

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Name EVO-STIK MITRE ADHESIVE PART A

Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use This product is a cyanoacrylate-based adhesive

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

#### 1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Respiratory irritation	

#### 2.2. Label elements

Contains ethyl-2-cyanoacrylate



United Kingdom - BE Page 1 / 13

# EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

#### Signal word

Warning

#### **Hazard statements**

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

#### **EU Specific Hazard Statements**

EUH202 - Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children

EUH208 - Contains 1,4-Benzenediol . May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other hazards

Polymerises with evolution of heat. Will bond to skin. Bonds skin and eyes in seconds. Harmful to aquatic life. Combustible liquid.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to	Specific concentration limit	M-Factor	M-Factor (long-ter	REACH registration
	,		Regulation (EC) No. 1272/2008 [CLP]	(SCL)		m)	number
ethyl-2-cyanoacrylate 80 - 100 %	230-391-5 (607-236-00- 9)	7085-85-0		STOT SE 3 :: C>=10%	·	·	01-2119527766- 29-XXXX
Hydroquinone 0.1 - <0.3 %	204-617-8 (604-005-00- 4)	123-31-9	Acute Tox. 4 (H302) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 2 (H351) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	10	1	01-2119524016- 51-XXXX

Full text of H- and EUH-phrases: see section 16

#### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

United Kingdom - BE Page 2 / 13

EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour - dust/mist -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
					mg/L		
ethyl-2-cyanoacrylate	230-391-5 (607-236-00-9)	7085-85-0	-	-	-	-	-
Hydroquinone	204-617-8 (604-005-00-4)	123-31-9	390	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If irritation persists or eye and/or

skin remains bonded: Get medical advice/attention.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical

attention immediately if symptoms occur.

Eye contact If eyelids are bonded closed or if skin to skin or skin to clothing bonding has occurred,

release bonding by covering affected area with a pad wetted with warm water. Do not force eyes or any bonded skin apart. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists or eye and/or skin remains bonded: Get medical advice/attention. Do not rub

affected area. Get medical attention if irritation develops and persists.

**Skin contact** Polymerises with evolution of heat. If eyelids are bonded closed or if skin to skin or skin

to clothing bonding has occurred, release bonding by covering affected area with a pad wetted with warm water. Do not force eyes or any bonded skin apart. If irritation persists or eye and/or skin remains bonded: Get medical advice/attention. Wash off immediately with soap and plenty of water for at least 15 minutes. Allow acetone or warm water to penetrate the bond and gently attempt to move bonded areas without pulling the skin

away from bonded area. Do not remove clothing if adhering to skin.

**Ingestion** Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin,

eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** May cause redness and tearing of the eyes. Burning sensation.

**Effects of Exposure** No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

### **SECTION 5: Firefighting measures**

United Kingdom - BE Page 3 / 13

**EVO-STIK MITRE ADHESIVE PART A** 

Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. In the event

of fire, cool tanks with water spray. Bonds skin and eyes in seconds.

Hazardous combustion products Nitrogen oxides (NOx).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Ensure adequate ventilation. Avoid contact

with skin, eyes or clothing.

**Other information** Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

**Methods for containment**Do not use cloths for mopping up. Flood with water to complete polymerization and

scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Use personal protection equipment. Do not eat, drink or smoke when using this product. See section 8 for more information. Take off contaminated clothing and wash it before reuse. Ensure adequate ventilation. Avoid breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory

equipment.

United Kingdom - BE Page 4 / 13

**EVO-STIK MITRE ADHESIVE PART A** Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 **Revision Number** 1.02

General hygiene considerations

Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this

product. Avoid contact with skin, eyes or clothing.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

Recommended storage

temperature

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C.

#### 7.3. Specific end use(s)

#### Specific use(s)

This product is a cyanoacrylate-based adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Exposure Limits**

Chemical name	European Union	United Kingdom
ethyl-2-cyanoacrylate	=	STEL: 0.3 ppm
7085-85-0		STEL: 1.5 mg/m <sup>3</sup>
Hydroquinone	-	TWA: 0.5 mg/m <sup>3</sup>
123-31-9		STEL: 1.5 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

<b>Derived No Effect Level (DNEL</b>	.)		
Hydroquinone (123-31-9)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	3.33 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2.1 mg/m³	

Derived No Effect Level (DN	EL)		
Hydroquinone (123-31-9)	•		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	1.66 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	1.05 mg/m³	
Consumer Long term Systemic health effects	Oral	0.6 mg/kg bw/d	

United Kingdom - BE Page 5 / 13

**EVO-STIK MITRE ADHESIVE PART A** Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

#### **Predicted No Effect Concentration** (PNEC)

Predicted No Effect Concentration (PNEC)	
Hydroquinone (123-31-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.57 μg/l
Freshwater - intermittent	1.34 μg/l
Marine water	0.057 μg/l
Freshwater sediment	0.0049 mg/kg dry weight
Marine sediment	0.00049 mg/kg dry weight
Soil	0.00064 mg/kg dry weight
Sewage treatment plant	0.71 mg/l

#### 8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be **Engineering controls** 

exhausted directly at the point of origin.

Personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Recommended Use:. Nitrile rubber. Glove thickness > 0.4 mm. Latex gloves. Hand protection

Polyethylene. Polypropylene. Glove thickness >= 0.15 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection Wear suitable protective clothing. Respiratory protection None under normal use conditions.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

**Physical state** Liquid Liquid **Appearance** Colour Colourless Odour Acrid.

Property Values Remarks • Method

Melting point / freezing point No data available None known

> 150 °C Initial boiling point and boiling

range

None known **Flammability** No data available Flammability Limit in Air None known

Upper flammability or explosive No data available

limits Lower flammability or explosive No data available

limits

> 85 °C Flash point

**Autoignition temperature** No data available None known **Decomposition temperature** None known

pН 6 - 7

No data available pH (as aqueous solution) None known Kinematic viscosity No data available None known

**Dynamic viscosity** No data available

Water solubility No data available. Polymerisation can occur

Solubility(ies) No data available None known **Partition coefficient** No data available None known No data available None known Vapour pressure Relative density No data available None known **Bulk density** No data available

United Kingdom - BE Page 6 / 13

**EVO-STIK MITRE ADHESIVE PART A** 

Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

Density 1.1 g/cm<sup>3</sup>

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

### SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** No information available.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

**Conditions to avoid** Protect from moisture.

10.5. Incompatible materials

Incompatible materials Alcohols. Alkali. Amines. Water.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

**Product Information** 

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Bonds skin and eyes in

United Kingdom - BE Page 7 / 13

EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

seconds. Causes serious eye irritation. (based on components). May cause redness,

itching, and pain.

**Skin contact** Specific test data for the substance or mixture is not available. Bonds skin and eyes in

seconds. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. May cause redness and tearing of the eyes.

Acute toxicity

**Numerical measures of toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >5000 mg/kg

 ATEmix (dermal)
 >5000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ethyl-2-cyanoacrylate	>5000 mg/kg (Rattus) OECD	>2000 mg/Kg (Oryctolagus	<21.1 mg/L (Rattus) 1 h
	401	cuniculus) OECD 402	- , ,
Hydroquinone	390 mg/kg (Rattus)	= 74800 mg/kg (Oryctolagus	-
		cuniculus)	

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information Hydroquinone (123-31-9)

Method	Species	Results
OECD Test No. 476: In Vitro Mammalian Cell	Mouse	Mutagenic
Gene Mutation Tests using the Hprt and xprt		
genes		

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Hydroquinone	Muta. 2

Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

United Kingdom - BE Page 8 / 13

EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

Component Information

Hydroquinone (123-31-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic	Rat	Limited evidence of a carcinogenic
Toxicity/Carcinogenicity Studies		effect

Chemical name	European Union
Hydroquinone	Carc. 2

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause respiratory irritation.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects No information available.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
ethyl-2-cyanoacrylate 7085-85-0	polymerizes	polymerizes	-	-		
Hydroquinone 123-31-9	EC50: =0.335mg/L (72h, Pseudokirchneri ella subcapitata)	LC50 96 h = 0.044 mg/L (Oncorhynchus mykiss flow-through)		EC50: =0.29mg/L (48h, Daphnia magna)	10	1

### 12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

United Kingdom - BE Page 9 / 13

**EVO-STIK MITRE ADHESIVE PART A** 

Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

**Component Information** 

Chemical name	Partition coefficient	
Hydroquinone	0.59	

#### 12.4. Mobility in soil

No information available. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
ethyl-2-cyanoacrylate	The substance is not PBT / vPvB
Hydroquinone	The substance is not PBT / vPvB

#### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

#### 12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

according to EWC

Waste codes / waste designations 15 01 10\*: Packaging containing residues of or contaminated by dangerous substances.

16 03 03\* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated

14.2 UN proper shipping name

14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

**Special Provisions** None

**IMDG** 

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated

United Kingdom - BE Page 10 / 13

### **EVO-STIK MITRE ADHESIVE PART A**

Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

14.3 Transport hazard class(es) Not regulated14.4 Packing group Not regulated

14.5 Marine pollutant NP
 14.6 Special precautions for user Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user Special Provisions None

#### Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

United Kingdom - BE Page 11 / 13

EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

#### National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

#### **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

H341 - Suspected of causing genetic defects

H351 - Suspected of causing cancer H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 16-Jul-2024

Indication of changes

**Revision note** SDS sections updated: 2.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

#### This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of

United Kingdom - BE Page 12 / 13

EVO-STIK MITRE ADHESIVE PART A Supercedes date 08-Aug-2023

Revision date 16-Jul-2024 Revision Number 1.02

its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 13 / 13



This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

### EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Name EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B

Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Activator

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

#### 1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### GB CLP (SI 2020/1567 as amended)

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 3 - (H412)
Aerosols	Category 1 - (H222, H229)

### 2.2. Label elements

Contains Isopropyl alcohol



United Kingdom - BE Page 1 / 15

### EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

#### Signal word

Danger

#### **Hazard statements**

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

#### **EU Specific Hazard Statements**

EUH208 - Contains N-tert-butylbenzothiazole-2-sulphenamide. May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P261 - Avoid breathing vapours/spray

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P405 - Store locked up

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

### Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. Harmful to aquatic life.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No (EU	CAS No	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Isopropyl alcohol	200-661-7	67-63-0	Eye Irrit. 2 (H319)	-	-	-	01-2119457558-
40 - <80 %	(603-117-00-		STOT SE 3 (H336)				25-XXXX
	0)		Flam. Liq. 2 (H225)				
Petroleum gases,	270-704-2	68476-85-7	Flam. Gas 1 (H220)	-	-	-	-
liquefied <0.1% w/w 1,3	(649-202-00-		Press. Gas (H280)				
Butadiene	6)						
>25 - <40 %							
N-tert-butylbenzothiazole	202-409-1	95-31-8	Skin Sens. 1 (H317)	-	-	-	01-2119492625-
-2-sulphenamide			Aquatic Acute 1 (H400)				29-xxxx
0.1- <1 %			Aquatic Chronic 1 (H410)				

United Kingdom - BE Page 2 / 15

### EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

					1
Full toxt of H and Ell	U phraces	caa caction	16		,

Full text of H- and EUH-phrases: see section 16

#### **Acute Toxicity Estimate**

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	
Isopropyl alcohol	200-661-7 (603-117-00-0)	67-63-0	-	-	-	-	-
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	270-704-2 (649-202-00-6)	68476-85-7	-	-	-	-	-
N-tert-butylbenzothiazo le-2-sulphenamide	202-409-1	95-31-8	-	7947.94	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### Notes

See section 16 for more information

Chemical name	Notes	
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene - 68476-85-7	K,S,U	

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**General advice** Show this safety data sheet to the doctor in attendance.

**Inhalation** Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

**Skin contact**Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

**Ingestion** Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a doctor.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin,

eyes or clothing.

United Kingdom - BE Page 3 / 15

**EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B** 

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour **Symptoms** 

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

No information available. **Effects of Exposure** 

4.3. Indication of any immediate medical attention and special treatment needed

No information available. Note to doctors

### **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Hazardous combustion products Carbon oxides.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See **Personal precautions** 

section 8 for more information. Avoid contact with skin, eves or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing

dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions** 

spillage if safe to do so. Prevent product from entering drains.

#### 6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce

vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

United Kingdom - BE 4 / 15 Page

EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections**See section 8 for more information. See section 13 for more information.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling

Please also refer to the SDS for the other component(s) of the kit. This product is part of a kit. Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** 

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep/store only in original container. Store in a dry place. Store in a closed container.

#### 7.3. Specific end use(s)

Specific use(s)

Activator.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Exposure Limits**

Chemical name	European Union	United Kingdom
Isopropyl alcohol	<b>=</b>	TWA: 400 ppm
67-63-0		TWA: 999 mg/m <sup>3</sup>
		STEL: 500 ppm
		STEL: 1250 mg/m <sup>3</sup>
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene		TWA: 1000 ppm

United Kingdom - BE Page 5 / 15

# **EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B Supercedes date** 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

68476-85-7	TWA: 1750 mg/m <sup>3</sup>
	STEL: 1250 ppm
	STEL: 2180 mg/m <sup>3</sup>

Chemical name	European Union	Ireland	United Kingdom
Isopropyl alcohol	=	40 mg/L (urine - Acetone end of	=
67-63-0		shift at end of workweek)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)						
Isopropyl alcohol (67-63-0)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Long term Systemic health effects	Inhalation	500 mg/m³				
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d				

N-tert-butylbenzothiazole-2-	N-tert-butylbenzothiazole-2-sulphenamide (95-31-8)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker Long term Systemic health effects	Inhalation	14 mg/m³				
worker Short term Systemic health effects	Inhalation	14 mg/m³				
worker Long term Local health effects	Inhalation	14 mg/kg bw/d				
worker Short term Local health effects	Inhalation	14 mg/m³				
worker Long term Systemic health effects	Dermal	67 mg/kg bw/d				

Derived No Effect Level (DN	Derived No Effect Level (DNEL)				
Isopropyl alcohol (67-63-0)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	89 mg/m³			
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d			

N-tert-butylbenzothiazole-2-sulphenamide (95-31-8)					
Туре	, ·	Derived No Effect Level (DNEL)	Safety factor		
Consumer	Inhalation	3.5 mg/m³			
Long term Systemic health effects					

United Kingdom - BE Page 6 / 15

### EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

Consumer Long term Local health effects	Inhalation	3.5 mg/m³	
Consumer Short term Local health effects	Inhalation	3.5 mg/m³	
Consumer Long term Systemic health effects	Dermal	33 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	266 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	1 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	8 mg/kg bw/d	

# Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)			
Isopropyl alcohol (67-63-0)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	140.9 mg/l		
Marine water	140.9 mg/l		
Sewage treatment plant	2251 mg/l		
Freshwater sediment	552 mg/kg dry weight		
Marine sediment	552 mg/kg dry weight		
Soil	28 mg/kg dry weight		

N-tert-butylbenzothiazole-2-sulphenamide (95-31-8)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.002 mg/l		
Marine water	0 mg/l		
Sewage treatment plant	100 mg/l		
Freshwater sediment	0.08 mg/kg dry weight		
Marine sediment	0.008 mg/kg dry weight		
Soil	0.796 mg/kg dry weight		

### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

**Hand protection** Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The

breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform

to standard EN 374

Skin and body protection Wear appropriate personal protective clothing to prevent skin contact.

**Respiratory protection** Ensure adequate respiratory protection during spray applications. In case of insufficient

ventilation, wear suitable respiratory equipment.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming

to EN 140 with Type A filter or better.

Environmental exposure controls No information available.

United Kingdom - BE Page 7 / 15

**EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B** 

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearanceAerosolColourColourlessOdourAlcohol.

Property Values Remarks • Method

Melting point / freezing point No data available None known

Initial boiling point and boiling Not applicable, Aerosol . Not applicable, Aerosol

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive 12.7

limits

Lower flammability or explosive 1.8

limits

Flash point Not applicable, Aerosol . Not applicable, Aerosol

Autoignition temperature399 °CNone knownDecomposition temperatureNone known

**bH** No data available Not applicable. Insoluble in water.

pH (as aqueous solution) No data available None known

Kinematic viscosity 2.2 mm<sup>2</sup>/s @ 40°C ISO 3104/3105

Dynamic viscosityNo data availableWater solubilityInsoluble in water.None knownSolubility(ies)Organic solventsNone knownPartition coefficientNo data availableNone known

Partition coefficientNo data availableNone knownVapour pressure412kPa @ 20 °CRelative density0.8None known

Bulk density No data available
Density No data available

Relative vapour density 2 @ 20 °C

**Particle characteristics** 

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content 695 g/L

#### 9.2.1. Information with regards to physical hazard classes

Not applicable

#### 9.2.2. Other safety characteristics

No information available

### SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** No information available.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

United Kingdom - BE Page 8 / 15

#### **EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B**

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge Yes.

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

#### 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

**Hazardous decomposition** 

products

None under normal use conditions. Stable under recommended storage conditions.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### **Product Information**

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause irritation

of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** May cause redness and tearing of the eyes. Inhalation of high vapour concentrations

may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Acute toxicity

#### **Numerical measures of toxicity**

#### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

#### **Component Information**

United Kingdom - BE Page 9 / 15

### **EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B**

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus	=72600 mg/m³ (Rattus) 4 h	
		cuniculus)		
Petroleum gases, liquefied	-	-	LD50 (4h) >20 mg/l (rattus)	
<0.1% w/w 1,3 Butadiene				
N-tert-butylbenzothiazole-2-sul	= 6850 mg/kg (Rattus)	> 7940 mg/kg (Oryctolagus	-	
phenamide		cuniculus )		

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information Isopropyl alcohol (67-63-0)

Method	Species	Results
OECD Test No. 476: In Vitro Mammalian Cell	Hamster, in vitro	Not mutagenic
Gene Mutation Tests using the Hprt and xprt		
genes		

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Petroleum gases, liquefied <0.1% w/w 1.3 Butadiene	Muta. 1B

#### Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union	
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	Carc. 1A	

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

United Kingdom - BE Page 10 / 15

**EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B** 

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

#### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

Note: PC-ADH-8 Multi-component adhesives and sealants Please also refer to the SDS for the

other component(s) of the kit This product is part of a kit

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Isopropyl alcohol	EC50 72 h >	LC50 96 h >	-	EC50:		, ,
67-63-0	1000 mg/L	1400000 ?g/L		=13299mg/L		
	(Desmodesmus	(Lepomis		(48h, Daphnia		
	subspicatus)	macrochirus)		magna)		
N-tert-butylbenzothiazo	EC50: >0.3mg/L	LC50: >0.3mg/L	-	EC50: >0.3mg/L		
le-2-sulphenamide	(96h,	(96h, Lepomis		(48h, Daphnia		
95-31-8	Pseudokirchneri	,		magna)		
	ella subcapitata)	LC50: >0.3mg/L				
		(96h,				
		Oncorhynchus				
		mykiss)				
		LC50: >0.3mg/L				
		(96h,				
		Pimephales				
		promelas)				

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

#### 12.3. Bioaccumulative potential

#### **Bioaccumulation**

**Component Information** 

Chemical name	Partition coefficient	
Isopropyl alcohol	0.05	
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	2.8	
N-tert-butylbenzothiazole-2-sulphenamide	3.36	

#### 12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment

United Kingdom - BE Page 11 / 15

#### **EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B**

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

Isopropyl alcohol	The substance is not PBT / vPvB
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	The substance is not PBT / vPvB
N-tert-butylbenzothiazole-2-sulphenamide	The substance is not PBT / vPvB

#### 12.6. Endocrine disrupting properties

No information available. **Endocrine disrupting properties** 

#### 12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or Contaminated packaging

weld containers.

according to EWC

Waste codes / waste designations 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product

**European Waste Catalogue** 16 05 04\* gases in pressure containers (including halons) containing dangerous

15 01 04 metallic packaging

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

### **SECTION 14: Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to Note:

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number UN1950 14.2 UN proper shipping name Aerosols 14.3 Transport hazard class(es) 2.2 Labels

Not regulated 14.4 Packing group

UN1950, Aerosols, 2, (E) Description

14.5 Environmental hazards No

14.6 Special precautions for user

**Special Provisions** 327, 625, 344, 190

Classification code 5A **Tunnel restriction code** (E) Limited quantity (LQ)

<u>IMDG</u>

UN1950 14.1 UN number or ID number 14.2 UN proper shipping name Aerosols 14.3 Transport hazard class(es) 2.1

Not regulated 14.4 Packing group

United Kingdom - BE Page 12 / 15

**EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B** 

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

**Description** UN1950, Aerosols, 2.1, (0°C c.c.)

14.5 Marine pollutant NF

14.6 Special precautions for user

**Special Provisions** 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ) See SP277 EmS-No. F-D, S-U

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

#### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950

14.2 UN proper shipping name Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

**Description** UN1950, Aerosols, flammable, 2.1

14.5 Environmental hazards No

14.6 Special precautions for user

Special Provisions A145, A167, A802

Limited quantity (LQ) 30 kg G ERG Code 10L

#### Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

#### Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Named dangerous substances per Seveso Directive (2012/18/EU)

United Kingdom - BE Page 13 / 15

#### **EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B**

Supercedes date 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene -	50	200
68476-85-7		

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

#### National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

#### **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

#### Notes relating to the identification, classification and labelling of substances

**Note K:** The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply

Note S: This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3)

**Note U (Table 3):** When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)

United Kingdom - BE Page 14 / 15

# **EVO-STIK MITRE ADHESIVE ACTIVATOR - Part B Supercedes date** 16-Nov-2022

Revision date 16-Jul-2024 Revision Number 1.02

IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 16-Jul-2024

Indication of changes

Revision note SDS sections updated, 3. Training Advice No information available Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 15 / 15