



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

LOCTITE SF 7503 known as Loctite 7503

SDS No. : 173263  
V003.0

Revision: 03.09.2018

printing date: 04.06.2020

Replaces version from: 28.04.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SF 7503 known as Loctite 7503

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Rust preventor

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

#### 2.2. Label elements

##### Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

##### Supplemental information

EUH210 Safety data sheet available on request.

Contains Isothiazolinone mixture 3:1 (CIT/MIT). May produce an allergic reaction.

##### Precautionary statement:

\*\*\*For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements\*\*\*

**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General chemical description:**

Primer

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2-Butoxyethanol 111-76-2	203-905-0 01-2119475108-36	1- < 5 %	Acute Tox. 4; Inhalation H332 Acute Tox. 4; Dermal H312 Acute Tox. 4; Oral H302 Eye Irrit. 2 H319 Skin Irrit. 2 H315
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	238-878-4	20- 40 %	
Tannins 1401-55-4	215-753-2	1- < 5 %	Skin Irrit. 2; Dermal H315 Eye Irrit. 2 H319 Aquatic Chronic 3 H412
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9		0,0002- < 0,0015 % ( 1,5 ppm- < 15 ppm)	Acute Tox. 2 H330 Acute Tox. 3 H301 Acute Tox. 2 H310 Skin Corr. 1B H314 Skin Sens. 1A H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 100 M factor (Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

**Ingestion:**

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Rust preventor

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Quartz (SiO <sub>2</sub> ) 14808-60-7 [SILICA, RESPIRABLE CRYSTALLINE]		0,1	Time Weighted Average (TWA):		EH40 WEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST, RESPIRABLE FRACTION]		0,1	Time Weighted Average (TWA):		EU OELIII
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	50	246	Short Term Exposure Limit (STEL):		EH40 WEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	25	123	Time Weighted Average (TWA):		EH40 WEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	20	98	Time Weighted Average (TWA):	Indicative	ECTLV
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	50	246	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		EH40 WEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL VAPOUR AND PARTICULATES]	150	474	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Quartz (SiO <sub>2</sub> ) 14808-60-7 [QUARTZ, RESPIRABLE DUST (SEE CRYSTALLINE SILICA)]		0,1	Time Weighted Average (TWA):		IR_OEL
Quartz (SiO <sub>2</sub> ) 14808-60-7 [RESPIRABLE CRYSTALLINE SILICA DUST, RESPIRABLE FRACTION]		0,1	Time Weighted Average (TWA):		EU OELIII
Silicon dioxide		6	Time Weighted Average		IR_OEL

112926-00-8 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]			(TWA):		
Silicon dioxide 112926-00-8 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL (EGBE)]	50	246	Short Term Exposure Limit (STEL):	Indicative OELV	IR_OEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL (EGBE)]	20	98	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL (EGBE)]			Skin designation:	Can be absorbed through the skin.	IR_OEL
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	20	98	Time Weighted Average (TWA):	Indicative	ECLTV
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	50	246	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		IR_OEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL (VAPOUR AND PARTICULATES)]	150	470	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2-Butoxyethanol 111-76-2	aqua (freshwater)		8,8 mg/l				
2-Butoxyethanol 111-76-2	aqua (marine water)		0,88 mg/l				
2-Butoxyethanol 111-76-2	sewage treatment plant (STP)		463 mg/l				
2-Butoxyethanol 111-76-2	sediment (freshwater)				34,6 mg/kg		
2-Butoxyethanol 111-76-2	sediment (marine water)				3,46 mg/kg		
2-Butoxyethanol 111-76-2	Soil				2,33 mg/kg		
2-Butoxyethanol 111-76-2	oral				20 mg/kg		
2-Butoxyethanol 111-76-2	aqua (intermittent releases)		9,1 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-Butoxyethanol 111-76-2	Workers	inhalation	Long term exposure - systemic effects		98 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	Workers	inhalation	Long term exposure - local effects		246 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	Workers	inhalation	Acute/short term exposure - systemic effects		1091 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	Workers	dermal	Long term exposure - systemic effects		125 mg/kg	
2-Butoxyethanol 111-76-2	Workers	dermal	Acute/short term exposure - systemic effects		89 mg/kg	
2-Butoxyethanol 111-76-2	General population	inhalation	Long term exposure - systemic effects		59 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	General population	inhalation	Acute/short term exposure - systemic effects		426 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	General population	inhalation	Acute/short term exposure - local effects		147 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	General population	dermal	Long term exposure - systemic effects		75 mg/kg	
2-Butoxyethanol 111-76-2	General population	dermal	Acute/short term exposure - systemic effects		89 mg/kg	
2-Butoxyethanol 111-76-2	General population	oral	Long term exposure - systemic effects		6,3 mg/kg	
2-Butoxyethanol 111-76-2	General population	oral	Acute/short term exposure - systemic effects		26,7 mg/kg	

**Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
2-Butoxyethanol 111-76-2 [2-BUTOXYETHANOL]	Butoxyacetic acid	Creatinine in urine	Sampling time: End of shift.		UKEH40BMG V		

**8.2. Exposure controls:**

Engineering controls:  
Ensure good ventilation/extraction.

Respiratory protection:  
Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Appearance	liquid liquid grey
Odor	mild
Odour threshold	No data available / Not applicable
pH ( )	3,0 - 3,5
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 100 °C (> 212 °F)
Flash point	> 100 °C (> 212 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density ( )	1,23 - 1,27 g/cm <sup>3</sup>
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Miscible
Solubility (qualitative) (Solvent: Acetone)	Partially soluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable  
max. VOC content:

68 g/l

**SECTION 10: Stability and reactivity****10.1. Reactivity**

None if used properly.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

Stable under normal conditions of storage and use.

**10.5. Incompatible materials**

None if used properly.

**10.6. Hazardous decomposition products**

carbon oxides.

**SECTION 11: Toxicological information****General toxicological information:**

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

**11.1. Information on toxicological effects****Acute oral toxicity:**

May cause irritation to the digestive tract.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-Butoxyethanol 111-76-2	LD50	1.746 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LD50	> 2.000 mg/kg	not specified	not specified
Tannins 1401-55-4	LD50	2.260 mg/kg	rat	not specified
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	66 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-Butoxyethanol 111-76-2	LD50	1.800 mg/kg	rabbit	
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LD50	> 2.000 mg/kg	not specified	not specified
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LD50	87,12 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)



**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,171 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	irritating	4 h	rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Category 1 (irreversible effects on the eye)		rabbit	not specified

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2-Butoxyethanol 111-76-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Butoxyethanol 111-76-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Butoxyethanol 111-76-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Butoxyethanol 111-76-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	ambiguous	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	in vitro mammalian chromosome aberration test	with and without		EPA OPP 84-2 (Mutagenicity Testing)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	positive	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	not applicable		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
2-Butoxyethanol 111-76-2	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		mouse	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: feed		Drosophila melanogaster	OECD Guideline 477 (Genetic Toxicology: Sex-linked Recessive Lethal Test in Drosophila melanogaster)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	negative	oral: gavage		rat	EPA OPP 84-2 (Mutagenicity Testing)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	not carcinogenic	oral: drinking water	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2-Butoxyethanol 111-76-2	NOAEL P 720 mg/kg NOAEL F1 720 mg/kg NOAEL F2 720 mg/kg	Two generation study	oral: drinking water	mouse	not specified
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL P 30 ppm NOAEL F1 300 ppm NOAEL F2 300 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2-Butoxyethanol 111-76-2	NOAEL 0,121 mg/l	inhalation	42 or 90 days 6 hours/day, 5 days/week	rat	not specified
2-Butoxyethanol 111-76-2	NOAEL < 69 mg/kg	oral: drinking water	91 d continous	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 16,3 mg/kg	oral: drinking water	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 0.34 mg/m3	inhalation: aerosol	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOAEL 2,625 mg/kg	oral: drinking water	90 d 6 h/d	rat	EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

**Aspiration hazard:**

No data available.

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	LC50	1.474 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Butoxyethanol 111-76-2	NOEC	> 100 mg/l	21 d	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	LC50	> 1.000 mg/l			OECD Guideline 203 (Fish, Acute Toxicity Test)
Tannins 1401-55-4	LC50	37 mg/l	96 h	Gambusia affinis	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	LC50	0,22 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,098 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	EC50	1.550 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC50	> 1.000 mg/l		Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,12 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	NOEC	100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,0036 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	EC50	1.840 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Butoxyethanol 111-76-2	NOEC	286 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC50	> 1.000 mg/l			OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC50	0,0052 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	NOEC	0,00064 mg/l	48 h	Skeletonema costatum	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Butoxyethanol 111-76-2	EC0	1.000 mg/l	30 min		not specified
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	EC0	> 1.000 mg/l			not specified
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	EC20	0,97 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

#### 12.2. Persistence and degradability

No data available.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2-Butoxyethanol 111-76-2	readily biodegradable	aerobic	73 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability/Closed Bottle Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

#### 12.3. Bioaccumulative potential

No data available.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	3,6			calculation	QSAR (Quantitative Structure Activity Relationship)

#### 12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
2-Butoxyethanol 111-76-2	0,81	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	-0,71 - 0,75	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
2-Butoxyethanol 111-76-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Quartz (SiO <sub>2</sub> ), <1% respirable 14808-60-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.

#### 12.6. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080111

**SECTION 14: Transport information**

- 14.1. UN number**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**  
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**  
not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %  
(2010/75/EC)

**VOC Paints and Varnishes (EU):**

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	A(g) Primer
Phase I (from 1.1.2007):	540 g/l
max. VOC content:	68 g/l

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**