



Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 4/19/2017 Revision date: 7/14/2023 Supersedes version of: 1/31/2022 Version: 8.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Rustins Quick Dry MDF Sealer
UFI : D6V5-XH8Q-Q81S-VE60
Product code : MDFS
Type of product : Paint
Synonyms : MDF SEALER
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : Adhesives, binding agents
Function or use category : Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Rustins Ltd
Waterloo raod
NW2 7TX London
United Kingdom
T +44 (0)208 450 4666 - F +44 (0)208 452 2008
rustins@rustins.co.uk - rustins.ltd

1.4. Emergency telephone number

Emergency number : +44 (0)208 450 4666
OFFICE HOURS ONLY MON. - FRI. 08:00 - 16:30

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H319 - Causes serious eye irritation.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

EUH-statements

: EUH208 - Contains 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE(55965-84-9). May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
BUTYL DIGLYCOL substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 112-34-5 EC-No.: 203-961-6 EC Index-No.: 603-096-00-8 REACH-no: 01-2119475104-44	$\geq 1 - < 5$	Eye Irrit. 2, H319
5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	< 0.1	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0.06 ≤C < 0.6) Skin Irrit. 2, H315 (0.06 ≤C < 0.6) Eye Irrit. 2, H319 (0.6 ≤C ≤ 100) Skin Corr. 1C, H314 (0.6 ≤C ≤ 100) Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing. Wash skin with plenty of water.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. None under normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

BUTYL DIGLYCOL (112-34-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-(2-Butoxyethoxy)ethanol
IOEL TWA	67.5 mg/m ³
IOEL TWA [ppm]	10 ppm
IOEL STEL	101.2 mg/m ³
IOEL STEL [ppm]	15 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Austria - Occupational Exposure Limits	
Local name	Butyldiglykol (Butoxydiethylenglykol; 2-(2-Butoxyethoxy)-ethanol; Diethylenglykolmonobutylether)
MAK (OEL TWA)	67.5 mg/m ³
MAK (OEL TWA) [ppm]	10 ppm
MAK (OEL STEL)	101.2 mg/m ³ (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	15 ppm (4x 15(Miw) min)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	2-(2-Butoxyéthoxy)éthanol # 2-(2-Butoxyethoxy)ethanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
OEL STEL [ppm]	15 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	2-(2-Бутокси-етокси) етанол
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi)etanol; dietilen-glikol monobutil-eter
GVI (OEL TWA) [1]	67.5 mg/m ³
GVI (OEL TWA) [2]	10 ppm
KGVI (OEL STEL)	101.2 mg/m ³
KGVI (OEL STEL) [ppm]	15 ppm
Remark	Direktiva: 2006/15/EZ
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	2-(2-Βουτοξυαιθοξυ)αιθανόλη
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
Czech Republic - Occupational Exposure Limits	
Local name	2-(2-Buthoxyethoxy)ethanol (Butyldiglykol)
PEL (OEL TWA)	70 mg/m ³
PEL (OEL TWA) [ppm]	10 ppm
NPK-P (OEL C)	100 mg/m ³
NPK-P (OEL C) [ppm]	15 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Butyldiglycol
OEL TWA [1]	68 mg/m ³

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
OEL TWA [2]	10 ppm
OEL STEL	101 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	E (betyder, at stoffet har en EF-grænseværdi)
Regulatory reference	BEK nr 202 af 21/02/2023
Finland - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi)etanoli
HTP (OEL TWA) [1]	68 mg/m ³
HTP (OEL TWA) [2]	10 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)éthanol
VME (OEL TWA)	67.5 mg/m ³
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	101.2 mg/m ³
VLE (OEL C/STEL) [ppm]	15 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2-(2-Butoxyethoxy)ethanol
AGW (OEL TWA) [1]	67 mg/m ³
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	1,5(I)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	2-(2-βουτοξυαιθοξυ) αιθανόλη
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	2-(2-BUTOXIETOXI)ETANOL
AK (OEL TWA)	67.5 mg/m ³
CK (OEL STEL)	101.2 mg/m ³
Remark	EU2 (2006/15/EK irányelvben közölt érték); T (Azok az anyagok, amelyek egészségkárosító hatása TARTÓS expozíciót követően jelentkeznek)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA [1]	67.5 mg/m ³
OEL TWA [2]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	2-(2-Butossietossi)etanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	2-(2-Butoksietoksi) etanols (butildiglikols)
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	2-(2-butoksietoksi)etanolis (dietilenglikolio monobutileteris, oksidietanolio monobutileteris)
IPRV (OEL TWA)	67.5 mg/m ³
IPRV (OEL TWA) [ppm]	10 ppm
TPRV (OEL STEL)	101.2 mg/m ³

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
TPRV (OEL STEL) [ppm]	15 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	2-(2-butoxyéthoxy)éthanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
TGG-8u (OEL TWA)	50 mg/m ³
TGG-8u (OEL TWA) [ppm]	7.4 ppm
TGG-15min (OEL STEL)	100 mg/m ³
TGG-15min (OEL STEL) [ppm]	14.8 ppm
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2023
Poland - Occupational Exposure Limits	
Local name	2-(2-Butoksyetoksy)etanol
NDS (OEL TWA)	67 mg/m ³
NDSch (OEL STEL)	100 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi) etanol (éter dietilenoglicol monobutílico)
OEL TWA [ppm]	10 ppm FIV (Fração inalável e vapor)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi)-etanol/Dowanol DB
OEL TWA	67.5 mg/m ³ 10 mg/m ³

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
OEL STEL	101.2 mg/m ³ 15 mg/m ³
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Serbia - Occupational Exposure Limits	
Local name	2-(2-бutoксиетокси)етанол; диетилен-гликол монобутил-етар
OEL TWA	68 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	EУ** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovakia - Occupational Exposure Limits	
Local name	Butyldiglykol 2-(2-butoxyetoxy)etanol
NPHV (OEL TWA) [1]	67.5 mg/m ³
NPHV (OEL TWA) [2]	10 ppm
NPHV (OEL STEL)	101.2 mg/m ³
NPHV (OEL STEL) [ppm]	15 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	2-(2-butoksietoksi)etanol (butildietilenglikol)
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	2-(2-Butoxietoxi) etanol (Dietilenglicol monobutiléter)
VLA-ED (OEL TWA) [1]	67.5 mg/m ³
VLA-ED (OEL TWA) [2]	10 ppm
VLA-EC (OEL STEL)	101.2 mg/m ³
VLA-EC (OEL STEL) [ppm]	15 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el “Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos” (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Dietylenglykolmonobutyleter
NGV (OEL TWA)	68 mg/m ³
NGV (OEL TWA) [ppm]	10 ppm
KTV (OEL STEL)	101 mg/m ³
KTV (OEL STEL) [ppm]	15 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
WEL TWA (OEL TWA) [1]	67.5 mg/m ³
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	101.2 mg/m ³
WEL STEL (OEL STEL) [ppm]	15 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	2-(2-bútoxýetoxý)etanól (bútýldíglýkól)
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
OEL STEL	101.2 mg/m ³
OEL STEL [ppm]	15 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	2-(2(butoksyetoksy)etanol
Grenseverdi (OEL TWA) [1]	68 mg/m ³
Grenseverdi (OEL TWA) [2]	10 ppm
Remark	E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	2-(2-бутоксietокси) етанол (бутилдиетиленгликол)
OEL TWA	67.5 mg/m ³
OEL TWA [ppm]	10 ppm
KTV	1.5
Short time value [mg/m ³]	101.25 mg/m ³
Short time value [ppm]	15 ppm

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BUTYL DIGLYCOL (112-34-5)	
Remark	(*) дополнување на граничната вредност заради донесената Директива на Комисијата 2006/15ES од 7 февруари 2006 за создавање на втора листа на индикативни гранични вредности за професионална изложеност според директивата 98/24/EC и за измените на директивата 91/322/EEC и директивата 2000/39/ EC (Сл. весник бр. 38 од ден 9.2.2006, стр. 36); (KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покосо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (EU) European Union – гранична вредност, определена на ниво на Европската унија
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија” бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Butyldiglycol / Butyldiglykol [Diethylenglykolmonobutylether]
MAK (OEL TWA) [1]	67 mg/m ³
MAK (OEL TWA) [2]	10 ppm
KZGW (OEL STEL)	101 mg/m ³
KZGW (OEL STEL) [ppm]	15 ppm
Critical toxicity	Rein, Sang, Foie / Niere, Blut, Leber
Notation	SS _c / SS _c
Regulatory reference	www.suva.ch, 01.01.2023

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Colorless watery liquid.
Odour	: Low.
Odour threshold	: Not available
Melting point	: No data available.
Freezing point	: Not available
Boiling point	: ≤ 100 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C
Auto-ignition temperature	: No data available.
Decomposition temperature	: Not available
pH	: 7.5-8.0
Viscosity, kinematic	: Not available
Solubility	: Material highly soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.0172 @ 20° C
Relative vapour density at 20°C	: No data available.
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

BUTYL DIGLYCOL (112-34-5)

LD50 dermal rabbit	2764 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 2090 - 3645
Skin corrosion/irritation	: Not classified pH: 7.5-8.0
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7.5-8.0
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

BUTYL DIGLYCOL (112-34-5)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified

BUTYL DIGLYCOL (112-34-5)

Viscosity, kinematic	≈ 6.794 mm ² /s
----------------------	----------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No known adverse effects on the functioning of water treatment plants under normal use conditions as recommended.

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

BUTYL DIGLYCOL (112-34-5)

LC50 - Fish [1]	1300 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

12.2. Persistence and degradability

Rustins Quick Dry MDF Sealer

Persistence and degradability : Not established.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Must follow special treatment according to local regulation. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Avoid release to the environment. Completely empty the packaging prior to decontamination. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN NOT CLASSIFIED	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN NOT CLASSIFIED	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VOC Directive (2004/42)

Organic solvent : Yes

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK) : WGK nwg, Non-hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Regulatory information.

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Training advice

: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2

Rustins Quick Dry MDF Sealer

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
EUH208	Contains 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE(55965-84-9). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.