



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK LEATHER ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Methyl ethyl ketone, Acetone, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW



SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Signal word

Danger

Hazard statements

H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.
H225 - Highly flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking
EUH205 - Contains epoxy constituents. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P261 - Avoid breathing mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P370 + P378 - In case of fire: Use dry chemical, CO₂, water spray or alcohol-resistant foam to extinguish
P403 + P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Methyl ethyl ketone	(606-002-00-3) 201-159-0	78-93-3	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119457290-43-XXXX
Acetone	(606-001-00-8) 200-662-2	67-64-1	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336)	-	01-2119471330-49-XXXX

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supercedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

				Flam. Liq. 2 (H225)		
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	1 - <5	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
-------------------------------------	---

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Hydrogen chloride.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

Recommended storage temperature Keep at temperatures between 5 and 25 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
Talc 14807-96-6	-	TWA: 1 mg/m ³ STEL: 3 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Methyl ethyl ketone 78-93-3	-	70 µmol/L (urine - Butan-2-one post shift)	70 µmol/L urine
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Methyl ethyl ketone (78-93-3)

Type	Exposure route	Derived No Effect Level	Safety factor
------	----------------	-------------------------	---------------

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

		(DNEL)	
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m ³	

Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m ³	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term	Oral	62 mg/kg bw/d	

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Systemic health effects			
-------------------------	--	--	--

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection

Tight sealing safety goggles. Face protection shield.

Hand protection

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection

Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Respiratory protection clothing.
In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour Colourless
Odour Characteristic.
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	56 °C	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	-20 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH (as aqueous solution)	No data available	Not applicable. Insoluble in water.
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supercedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Acetone (67-64-1)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		

12.2. Persistence and degradability

Persistence and degradability No information available.

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone	0.3

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Acetone	-0.24
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
Methyl ethyl ketone	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB PBT assessment does not apply
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	640C
Classification code	F1

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Tunnel restriction code (D/E)
Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler Number) 33

IMDG

14.1 UN number or ID number UN1133
14.2 Proper Shipping Name Adhesives
14.3 Transport hazard class(es) 3
14.4 Packing group II
Description UN1133, Adhesives, 3, II, (-20°C c.c.)
14.5 Marine pollutant NP
14.6 Special Provisions None
Limited Quantity (LQ) 5 L
EmS-No F-E, S-D
14.7 Maritime transport in bulk according to IMO instruments Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1133
14.2 Proper Shipping Name Adhesives
14.3 Transport hazard class(es) 3
14.4 Packing group II
Description UN1133, Adhesives, 3, II
14.5 Environmental hazards Not applicable
14.6 Special Provisions A3
Limited quantity (LQ) 1 L
ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009
Not applicable

Persistent Organic Pollutants
Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

SAFETY DATA SHEET

BOSTIK LEATHER ADHESIVE
Supersedes Date: 24-Apr-2020

Revision date 15-Dec-2022
Revision Number 1.02

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 15-Dec-2022

Indication of changes

Revision note SDS sections updated, 3, 8.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet