

## SAFETY DATA SHEET

### Swarfega Jizer Aerosol

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Swarfega Jizer Aerosol  
**Product number** SJZ500ML, SJZ500SFX

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Detergent. Car maintenance product.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** SC Johnson Professional Ltd  
Denby Hall Way  
Denby  
Derbyshire  
DE5 8JZ  
+44 (0) 1773 855100  
info.prouk@scj.com

##### 1.4. Emergency telephone number

**Emergency telephone** National Poisons Information Service (UK) 0344 8920111 (Health Professionals only)

#### SECTION 2: Hazards identification


##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** STOT SE 3 - H336  
**Environmental hazards** Not Classified

##### 2.2. Label elements

###### Hazard pictograms



**Signal word** Danger

**Hazard statements** H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated.  
H336 May cause drowsiness or dizziness.

**Precautionary statements** P102 Keep out of reach of children.  
P261 Avoid breathing vapour/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves.  
P501 Dispose of contents/ container in accordance with national regulations.

## Swarfega Jizer Aerosol

|   |   |
|---|---|
| <b>Supplemental label information</b>         | EUH066 Repeated exposure may cause skin dryness or cracking.  |
| <b>Contains</b>                               | HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS  |
| <b>Detergent labelling</b>                    | ≥ 30% aliphatic hydrocarbons, < 5% aromatic hydrocarbons, < 5% non-ionic surfactants  |
| <b>Supplementary precautionary statements</b> | <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> |

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

|   |
|---|
| <b>HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, &lt; 2% AROMATICS</b> <span style="float: right;"><b>60-100%</b></span>  |
| CAS number: 64742-48-9                      EC number: 919-857-5  |
| <b>Classification</b><br>Flam. Liq. 3 - H226<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304  |
| <b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b> <span style="float: right;"><b>10-30%</b></span>   |
| CAS number: 68476-85-7                      EC number: 270-704-2  |
| <b>Classification</b><br>Flam. Gas 1A - H220<br>Press. Gas (Liq.) - H280  |
| <b>XYLENE</b> <span style="float: right;"><b>1-10%</b></span>   |
| CAS number: 1330-20-7                      EC number: 215-535-7                      REACH registration number: 01-2119488216-32-XXXX   |
| <b>Classification</b><br>Flam. Liq. 3 - H226<br>Acute Tox. 4 - H312<br>Acute Tox. 4 - H332<br>Skin Irrit. 2 - H315<br>Eye Irrit. 2 - H319<br>STOT SE 3 - H335<br>STOT RE 2 - H373<br>Asp. Tox. 1 - H304 |

## Swarfega Jizer Aerosol

|                       |                      |
|-----------------------|----------------------|
| <b>ETHYLBENZENE</b>   | <b>&lt;1%</b>        |
| CAS number: 100-41-4  | EC number: 202-849-4 |
| <b>Classification</b> |                      |
| Flam. Liq. 2 - H225   |                      |
| Acute Tox. 4 - H332   |                      |

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                            |   |
|----------------------------|---|
| <b>General information</b> | Move affected person to fresh air at once. Get medical attention if any discomfort continues.   |
| <b>Inhalation</b>          | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. Place unconscious person on their side in the recovery position and ensure breathing can take place. |
| <b>Ingestion</b>           | Rinse mouth thoroughly with water. Get medical attention if any discomfort continues. Do not induce vomiting unless under the direction of medical personnel. Show this Safety Data Sheet to the medical personnel.   |
| <b>Skin contact</b>        | Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.  |
| <b>Eye contact</b>         | Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.   |

#### 4.2. Most important symptoms and effects, both acute and delayed

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | Spray/mists may cause respiratory tract irritation.  |
| <b>Ingestion</b>    | Due to the physical nature of this product, it is unlikely that ingestion will occur.  |
| <b>Skin contact</b> | Repeated exposure may cause skin dryness or cracking.  |
| <b>Eye contact</b>  | Vapour or spray in the eyes may cause irritation and smarting. Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. |

#### 4.3. Indication of any immediate medical attention and special treatment needed

|                             |                              |
|-----------------------------|------------------------------|
| <b>Notes for the doctor</b> | No specific recommendations. |
|-----------------------------|------------------------------|

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

|                                       |   |
|---------------------------------------|---|
| <b>Suitable extinguishing media</b>   | Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist. |
| <b>Unsuitable extinguishing media</b> | Do not use water jet as an extinguisher, as this will spread the fire.                                    |

#### 5.2. Special hazards arising from the substance or mixture

|                                      |  |
|--------------------------------------|--|
| <b>Specific hazards</b>              | Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. Vapours may form explosive mixtures with air. |
| <b>Hazardous combustion products</b> | Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO).  |

#### 5.3. Advice for firefighters

## Swarfega Jizer Aerosol

|  |  |
|--|--|
| <b>Protective actions during firefighting</b>        | Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. |
| <b>Special protective equipment for firefighters</b> | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.   |

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Avoid contact with skin, eyes and clothing. Protect from freezing and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

##### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Sk

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

##### **ETHYLBENZENE**

## Swarfega Jizer Aerosol

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

**Ingredient comments** WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment



**Appropriate engineering controls** Provide adequate general and local exhaust ventilation.

**Eye/face protection** Not required normally but wear eye protection if you are conducting an operation where there is a risk of this product getting in the eyes. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

**Hand protection** To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

**Other skin and body protection** Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**Hygiene measures** Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**Respiratory protection** Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                     |
|---|---------------------|
| <b>Appearance</b>                                   | Aerosol.            |
| <b>Colour</b>                                       | Yellowish           |
| <b>Odour</b>  | Characteristic.     |
| <b>pH</b>   | Not determined.     |
| <b>Melting point</b>                                | Not determined.     |
| <b>Initial boiling point and range</b>              | -40 - -2°C (LPG)    |
| <b>Flash point</b>                                  | -104°C (LPG)        |
| <b>Evaporation rate</b>                             | Not determined.     |
| <b>Upper/lower flammability or explosive limits</b> | 1.4 - 10.9%(V)(LPG) |

## Swarfega Jizer Aerosol

|                           |                       |
|---------------------------|-----------------------|
| Vapour pressure           | Not determined.       |
| Vapour density            | Not determined.       |
| Relative density          | Not relevant.         |
| Solubility(ies)           | Immiscible with water |
| Auto-ignition temperature | 365 °C / 689 °F (LPG) |
| Decomposition Temperature | Not relevant.         |
| Viscosity                 | Not relevant.         |
| Oxidising properties      | Not available.        |

### 9.2. Other information

|                   |       |
|-------------------|-------|
| Other information | None. |
|-------------------|-------|

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

|            |   |
|------------|---|
| Reactivity | There are no known reactivity hazards associated with this product. |
|------------|---|

### 10.2. Chemical stability

|           |  |
|-----------|--|
| Stability | Stable at normal ambient temperatures. |
|-----------|--|

### 10.3. Possibility of hazardous reactions

|                                    |               |
|------------------------------------|---------------|
| Possibility of hazardous reactions | Not relevant. |
|------------------------------------|---------------|

### 10.4. Conditions to avoid

|                     |   |
|---------------------|---|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:<br>Strong oxidising agents. Strong alkalis. Strong mineral acids. |
|---------------------|---|

### 10.5. Incompatible materials

|                    |   |
|--------------------|---|
| Materials to avoid | Strong acids. Strong alkalis. Strong reducing agents. |
|--------------------|---|

### 10.6. Hazardous decomposition products

|                                  |  |
|----------------------------------|--|
| Hazardous decomposition products | Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). |
|----------------------------------|--|

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - dermal

|                    |           |
|--------------------|-----------|
| ATE dermal (mg/kg) | 58,666.67 |
|--------------------|-----------|

#### Acute toxicity - inhalation

|                            |           |
|----------------------------|-----------|
| ATE inhalation (gases ppm) | 240,000.0 |
|----------------------------|-----------|

|                               |        |
|-------------------------------|--------|
| ATE inhalation (vapours mg/l) | 586.67 |
|-------------------------------|--------|

|                                   |      |
|-----------------------------------|------|
| ATE inhalation (dusts/mists mg/l) | 80.0 |
|-----------------------------------|------|

|            |  |
|------------|--|
| Inhalation | May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. |
|------------|--|

## Swarfega Jizer Aerosol

|                          |   |
|--------------------------|---|
| <b>Skin contact</b>      | Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. |
| <b>Eye contact</b>       | Irritating to eyes.   |
| <b>Route of exposure</b> | Inhalation Skin and/or eye contact  |

### SECTION 12: Ecological information

**Ecotoxicity** Dangerous for the environment if discharged into watercourses.

#### 12.1. Toxicity

**Toxicity** The product is not believed to present a hazard due to its physical nature.

#### 12.2. Persistence and degradability

**Persistence and degradability** Volatile substances are degraded in the atmosphere within a few days. The other substances in the product are expected to be readily biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Bioaccumulation is unlikely to be significant because of the low water-solubility of this product. Exposure to aquatic environment unlikely.

#### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Only experts should be permitted to carry out disposal of this material.

**Disposal methods** Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** AEROSOLS, Flammable, Class 2.1, (D).

**Proper shipping name (IMDG)** AEROSOLS, Flammable, Class 2.1, (D).

## Swarfega Jizer Aerosol

**Proper shipping name (ICAO)** AEROSOLS, Flammable, Class 2.1, (D).

**Proper shipping name (ADN)** AEROSOLS, Flammable, Class 2.1, (D).

### 14.3. Transport hazard class(es)

|                                    |     |
|------------------------------------|-----|
| <b>ADR/RID class</b>               | 2.1 |
| <b>ADR/RID classification code</b> | 5F  |
| <b>ADR/RID label</b>               | 2.1 |
| <b>IMDG class</b>                  | 2.1 |
| <b>ICAO class/division</b>         | 2.1 |
| <b>ADN class</b>                   | 2.1 |

### Transport labels



### 14.4. Packing group

|                              |      |
|------------------------------|------|
| <b>ADR/RID packing group</b> | None |
| <b>IMDG packing group</b>    | None |
| <b>ICAO packing group</b>    | None |
| <b>ADN packing group</b>     | None |

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

|                                |          |
|--------------------------------|----------|
| <b>EmS</b>                     | F-D, S-U |
| <b>ADR transport category</b>  | 2        |
| <b>Tunnel restriction code</b> | (D)      |

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78  
and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

|                             |   |
|-----------------------------|---|
| <b>National regulations</b> | The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).<br>EH40/2005 Workplace exposure limits.<br>The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. |
|-----------------------------|---|



## Swarfega Jizer Aerosol

### EU legislation

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

|                                  |   |
|----------------------------------|---|
| <b>Revision comments</b>         | Revision of information NOTE: Lines within the margin indicate significant changes from the previous revision.  |
| <b>Revision date</b>             | 02/11/2021  |
| <b>Revision</b>                  | 9   |
| <b>Supersedes date</b>           | 01/11/2021  |
| <b>Hazard statements in full</b> | <p>H220 Extremely flammable gas.<br/> H222 Extremely flammable aerosol.<br/> H225 Highly flammable liquid and vapour.<br/> H226 Flammable liquid and vapour.<br/> H229 Pressurised container: may burst if heated.<br/> H280 Contains gas under pressure; may explode if heated.<br/> H304 May be fatal if swallowed and enters airways.<br/> H312 Harmful in contact with skin.<br/> H315 Causes skin irritation.<br/> H319 Causes serious eye irritation.<br/> H332 Harmful if inhaled.<br/> H335 May cause respiratory irritation.<br/> H336 May cause drowsiness or dizziness.<br/> H373 May cause damage to organs through prolonged or repeated exposure.</p> |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.