

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers  
 Synonyms : DURA-INK® 5 Black / DURA-INK® 15 Black / DURA-INK® 25 Black / DURA-INK® 55 Black / DURA-INK® 60 Black / DURA-INK® 200 Black

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Professional use, Industrial use  
 Use of the substance/mixture : Marking

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

LA-CO Industries Europe S.A.S.  
 Parc Industriel de la Plaine de  
 l'Ain - Allée des Combes.  
 01150.BLYES.France.  
 Phone: +33 (0)4 74 46 23 23  
 Fax: +33 (0)4 74 46 23 29  
 E-mail: info@eu.laco.com  
 Web: http://www.markal.com

**1.4. Emergency telephone number**

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flam. Liq. 3 H226  
 Eye Dam. 1 H318  
 STOT SE 3 H336  
 STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



Signal word (CLP) : Danger  
 Hazardous ingredients : 1-Methoxy-2-propanol; propan-1-ol  
 Hazard statements (CLP) : H226 - Flammable liquid and vapour  
 H318 - Causes serious eye damage  
 H335 - May cause respiratory irritation  
 H336 - May cause drowsiness or dizziness  
 Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P233 - Keep container tightly closed  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical, lighting, ventilating equipment  
 P261 - Avoid breathing mist, spray, vapours  
 P271 - Use only outdoors or in a well-ventilated area  
 P280 - Wear eye protection, protective gloves  
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER/doctor  
P312 - Call a poison center or doctor if you feel unwell  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, Water spray to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to an authorised waste collection point

### 2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-Methoxy-2-propanol	(CAS No) 107-98-2 (EC no) 203-539-1 (EC index no) 603-064-00-3	25 - 50	Flam. Liq. 3, H226 STOT SE 3, H336
propan-1-ol	(CAS No) 71-23-8 (EC no) 200-746-9 (EC index no) 603-003-00-0	25 - 50	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336

Full text of R- and H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Call a POISON CENTER or doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May cause respiratory irritation.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : Like any product not designed to be ingested, this product may cause stomach distress if ingested in large quantities.

### 4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Water spray.
- Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. In case of fire: stop leak if safe to do so. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing. EN469.

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

##### 6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Clothing impervious to chemical penetration. Wear suitable gloves resistant to chemical penetration. In case of inadequate ventilation wear respiratory protection.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves. Chemical goggles or safety glasses. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment.

Emergency procedures : Ventilate area. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb and/or contain spill with inert material, then place in suitable container.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. Avoid breathing mist, spray, vapours. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharge.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.

Storage conditions : Keep in fireproof place. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

Incompatible products : Strong oxidizers.

Incompatible materials : Heat sources. Sources of ignition.

Prohibitions on mixed storage : Keep away from incompatible materials.

#### 7.3. Specific end use(s)

Marking.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

1-Methoxy-2-propanol (107-98-2)		
EU	IOELV TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	150 ppm
EU	Notes	Skin
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	150 ppm
propan-1-ol (71-23-8)		
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	625 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	250 ppm

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

### propan-1-ol (71-23-8)

United Kingdom

Remark (WEL)

(Sk)

#### 8.2. Exposure controls

Appropriate engineering controls	: Avoid creating mist or spray. Avoid splashing. Eyewash stations. Provide local exhaust ventilation of closed transfer systems to minimize exposures.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves resistant to chemical penetration. Impermeable protective nitrile gloves. EN 374.
Eye protection	: In case of splashing or aerosol production: protective goggles. Chemical goggles or safety glasses. EN 166.
Skin and body protection	: Wear suitable protective clothing. Impervious clothing. EN702.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use an approved respirator equipped with oil/mist cartridges. EN 12083.
Other information	: Do not eat, drink or smoke when using this product.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Black.
Odour	: No data available
Odour threshold	: No data available
pH	: 5.7 @ 20 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 96 °C
Flash point	: 23 °C
Auto-ignition temperature	: 287 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour, Flammable liquid and vapour
Vapour pressure	: 14 mm Hg @ 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.9 g/cm <sup>3</sup> @ 20 °C
Solubility	: Miscible with water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 5 mPa.s @ 20 °C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.7 vol % 13.5 g/m <sup>3</sup>

#### 9.2. Other information

VOC content : 82 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known.

#### 10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture. Flammable liquid and vapour.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Avoid excessive heat or cold. Direct sunlight. Heat. Keep away from sources of ignition. Open flame. Overheating. Sparks.

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

May release flammable gases. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Not classified (Based on available data, the classification criteria are not met)

1-Methoxy-2-propanol (107-98-2)	
LD50 oral rat	4016 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 inhalation rat (ppm)	> 7000 ppm 6 hr
ATE CLP (oral)	4016.000 mg/kg bodyweight

propan-1-ol (71-23-8)	
LD50 oral rat	5400 mg/kg
LD50 dermal rabbit	4032 mg/kg
LC50 inhalation rat (mg/l)	> 33.8 mg/l/4h
ATE CLP (oral)	5400.000 mg/kg bodyweight
ATE CLP (dermal)	4032.000 mg/kg bodyweight

**Skin corrosion/irritation** : Not classified

pH: 5.7 @ 20 °C

**Serious eye damage/irritation** : Causes serious eye damage.

pH: 5.7 @ 20 °C

**Respiratory or skin sensitisation** : Not classified (Based on available data, the classification criteria are not met)

**Germ cell mutagenicity** : Not classified

**Carcinogenicity** : Not classified (Based on available data, the classification criteria are not met)

**Reproductive toxicity** : Not classified (Based on available data, the classification criteria are not met)

**Specific target organ toxicity (single exposure)** : May cause drowsiness or dizziness. May cause respiratory irritation.

May cause respiratory irritation  
May cause drowsiness or dizziness

**Specific target organ toxicity (repeated exposure)** : Not classified (Based on available data, the classification criteria are not met)

**Aspiration hazard** : Not classified (Based on available data, the classification criteria are not met)

## SECTION 12: Ecological information

### 12.1. Toxicity

1-Methoxy-2-propanol (107-98-2)	
LC50 fish 1	20800 mg/l
EC50 Daphnia 1	23300 mg/l
ErC50 (algae)	> 1000 mg/l

propan-1-ol (71-23-8)	
LC50 fish 1	4555 mg/l 96 h
EC50 Daphnia 1	1000 mg/l 48 h

### 12.2. Persistence and degradability

DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers	
Persistence and degradability	May cause long-term adverse effects in the environment.

1-Methoxy-2-propanol (107-98-2)	
Persistence and degradability	Readily biodegradable.
Biodegradation	96 % 28 d

propan-1-ol (71-23-8)	
Persistence and degradability	Readily biodegradable.
Biodegradation	75 % 20 d

### 12.3. Bioaccumulative potential

1-Methoxy-2-propanol (107-98-2)	
Bioaccumulative potential	Not expected to bioaccumulate.

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

propan-1-ol (71-23-8)	
BCF fish 1	0.88
Log Pow	0.2

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers
PBT: not yet assessed
vPvB: not yet assessed

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 00 - wastes from MFSU and removal of paint and varnish 08 01 13* - sludges from paint or varnish containing organic solvents or other dangerous substances
H code	: H3-B - 'Flammable': liquid substances and preparations having a flash point equal to or greater than 21 °C and less than or equal to 55 °C H4 - 'Irritant': non-corrosive substances and preparations which, through immediate, prolonged or repeated contact with the skin or mucous membrane, can cause inflammation H5 - 'Harmful': substances and preparations which, if they are inhaled or ingested or if they penetrate the skin, may involve limited health risks

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

Not considered a dangerous good for transport regulations

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) :

### 14.3. Transport hazard class(es)

Not applicable

### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

No additional information available

#### 14.6.2. Transport by sea

No additional information available

#### 14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 82 %

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

according to Regulation (EU) 2015/830

Indication of changes:

Original Document.

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	DNEL: Derived No Effect Level
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	NOEC: No Observable Effect Concentration
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	PNEC: Predicted No Effect Level
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average

Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.  
European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition.  
OSHA 29CFR 1910.1200 Hazard Communication Standard.  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H318	Causes serious eye damage
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
R10	Flammable
R11	Highly flammable
R41	Risk of serious damage to eyes
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable

# DURA-INK® 5, 15, 25, 55, 60, 200 Black Markers

## Safety Data Sheet

according to Regulation (EU) 2015/830

Xi	Irritant
----	----------

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Expert judgment
STOT SE 3	H335	Expert judgment

LA-CO EU CLP SDS United Kingdom

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*