



SAFETY DATA SHEET TETRION HARD AS ROCK

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	TETRION HARD AS ROCK
Product number	TSF200, TSF204
UFI	UFI: 4SVQ-FQ9P-A71X-GVR3

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier	TETROSYL EUROPE 79 rue du chemin vert 59.273 Fretin TEL: 03 20 28 06 30 qualite@tetrosyl-france.com
----------	---

Manufacturer	TETROSYL LIMITED Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com
--------------	---

1.4. Emergency telephone number

Emergency telephone	+44 (0)161 764 5981
---------------------	---------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards	Not Classified
Health hazards	Skin Irrit. 2 - H315 Eye Dam. 1 - H318
Environmental hazards	Not Classified

2.2. Label elements

Hazard pictograms



Signal word	Danger
-------------	--------

Hazard statements	H315 Causes skin irritation. H318 Causes serious eye damage.
-------------------	---

TETRION HARD AS ROCK

Precautionary statements	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P264 Wash contaminated skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor. P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.
Supplemental label information	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
UFI	UFI: 4SVQ-FQ9P-A71X-GVR3
Contains	CALCIUM ALUMINATE, CALCIUM FORMATE
Supplementary precautionary statements	P321 Specific treatment (see medical advice on this label).

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

CALCIUM ALUMINATE CAS number: 65997-16-2 EC number: 266-045-5	30-<60%
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318	
CALCIUM CARBONATE CAS number: 1317-65-3 EC number: 215-279-6	10-<30%
Classification Not Classified	
CALCIUM FORMATE CAS number: 544-17-2 EC number: 208-863-7	3-<5.0%
Classification Eye Dam. 1 - H318	
FINE CASTING PLASTER CAS number: 26499-65-0 EC number: 231-900-3	2-<3%
Classification Not Classified	

TETRION HARD AS ROCK

TITANIUM DIOXIDE			2-<3%
CAS number: 13463-67-7	EC number: 236-675-5	UK REACH registration number: UK-01-7336197506-0-0000	
Classification Not Classified			

KAOLINITE			0.1-<0.3%
CAS number: 1332-58-7	EC number: 310-127-6		
Classification Not Classified			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination. Effects may be delayed. Keep affected person under observation. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Inhalation	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Get medical attention if any discomfort continues.
Eye contact	Important! Immediately rinse with water for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	May cause an asthma-like shortness of breath. Upper respiratory irritation. Inhalation of dusts during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause chemical burns in mouth and throat. Metallic taste.
Skin contact	Skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Blistering may occur. Burns can occur.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

TETRION HARD AS ROCK

5.2. Special hazards arising from the substance or mixture

Specific hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	No known hazardous decomposition products.

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
---	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8. Avoid contact with skin and eyes. Avoid inhalation of dust.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Avoid generation and spreading of dust. Remove spillage with vacuum cleaner or collect with a shovel and broom, or similar.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Avoid eating, drinking and smoking when using the product. Avoid handling which leads to dust formation. Avoid inhalation of dust and contact with skin and eyes.
--------------------------	---

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	No specific recommendations.
----------------------------	------------------------------

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust
 Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust
 Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust
 Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust
 Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust
 Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

FINE CASTING PLASTER

TETRION HARD AS ROCK

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

KAOLINITE

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³ respirable dust

WEL = Workplace Exposure Limit.

TARTARIC ACID (CAS: 87-69-4)

DNEL

Workers - Dermal; Long term systemic effects: 2.9 mg/kg

Workers - Inhalation; Long term systemic effects: 5.2 mg/m³

General population - Dermal; Long term systemic effects: 1.5 mg/kg

General population - Inhalation; Long term systemic effects: 1.3 mg/m³

General population - Oral; Long term systemic effects: 8.1 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of dust. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Dust-resistant, chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber.

Other skin and body protection

Provide eyewash station.

Hygiene measures

When using do not eat, drink or smoke. Wash hands after contact. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	Grey.
Odour	Odourless.
Melting point	Not determined.
Initial boiling point and range	Scientifically unjustified.
Evaporation rate	Not determined.

TETRION HARD AS ROCK

Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.1 @ 20°C
Solubility(ies)	Soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.

9.2. Other information

Other information	None.
-------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Reactions with the following materials may generate heat: Water.
------------	--

10.2. Chemical stability

Stability	No particular stability concerns. The substance is hygroscopic and will absorb water by contact with the moisture in the air.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not applicable.
------------------------------------	-----------------

10.4. Conditions to avoid

Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No information available.
Acute and chronic health hazards	This product may cause skin and eye irritation. Dust may irritate the respiratory system.

SECTION 12: Ecological information

Ecotoxicity	Dangerous for the environment if discharged into watercourses.
-------------	--

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish	Not available.
-----------------------	----------------

TETRION HARD AS ROCK

Acute toxicity - aquatic invertebrates Not available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

TETRION HARD AS ROCK

Transport in bulk according to Not applicable.
Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Regulatory Department
Revision date	22/06/2022
Revision	5
Supersedes date	24/01/2022
SDS number	34058
SDS status	Approved.
Hazard statements in full	H315 Causes skin irritation. H318 Causes serious eye damage.