

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 10/5/2012 Revision date: 2/22/2024 Supersedes version of: 7/31/2023 Version: 16.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

: Rustins Paint Driers (Terebene) Trade name UFI : 5FA0-P3M7-F00G-VD6S

: PAID Product code Type of product : Solvents Synonyms : PAINT DRIERS Product group : End product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use, Professional use

#### 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

Distributor Supplier Rustins Ltd Excellence Ltd Waterloo raod 43 Grange Parade,

NW2 7TX London Unit 43

Baldoyle Industrial Estate, United Kingdom T +442084504666, F +44 (0)208 452 2008 D13 Y860 Dublin

rustins@rustins.co.uk, rustins.ltd Ireland

T 00353 (0)1 8323300, F 00353 (0)1 8323584 Orders@excellence.ie, www.excellence.ie

### 1.4. Emergency telephone number

: +44(0)2084504666 **Emergency number** 

OFFICE HOURS ONLY MON. - FRI. 08:00 - 16.30

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
New Zealand	Local Poison Centre	Invercargill	0800 764 766	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226 Serious eye damage/eye irritation, Category 1 H318 Skin sensitisation, Category 1 H317 H340 Germ cell mutagenicity, Category 1B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carcinogenicity, Category 1B H350
Reproductive toxicity, Category 2 H361
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)









Signal word (CLP)

Contains

: Danger

COBALT 6 %; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics; butan-1-ol; n-butanol; Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics; Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]

Hazard statements (CLP)

Precautionary statements (CLP)

**EUH-statements** 

: H226 - Flammable liquid and vapour.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects.

H350 - May cause cancer.

H361 - Suspected of damaging the unborn child. (if swallowed).

: P102 - Keep out of reach of children.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P312 - Call a POISON CENTRE or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

: EUH066 - Repeated exposure may cause skin dryness or cracking.

2/22/2024 (Revision date) EN (English) 2/16

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9 EC-No.: 919-857-5 EC Index-No.: 649-327-00-6 REACH-no: 01-2119463258- 33	≥ 65 – < 70	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 64742-48-9: Naphtha (petroleum), hydrotreated heavy EC-No.: 918-481-9 REACH-no: 01-2119457273-	1.65 – 7.98	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119455851- 35	≥ 5 – < 10	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
calcium bis(2-ethylhexanoate)	CAS-No.: 136-51-6 EC-No.: 205-249-0 REACH-no: 01-2119978297- 19	< 5	Aquatic Chronic 3, H412
butan-1-ol; n-butanol substance with national workplace exposure limit(s) (GB, IE)	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6 REACH-no: 01-2119484630-38	≥1-<5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
COBALT 6 %	CAS-No.: 13586-82-8	≥1-<5	Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361f

Full text of H- and EUH-statements: see section 16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin

irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Repeated exposure may cause skin dryness or

cracking.

Symptoms/effects after eye contact : Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Hazardous decomposition products in case of fire : Toxic fumes may be released.

## 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

## 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

# 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

2/22/2024 (Revision date) EN (English) 4/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid

breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

: Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

**Switzerland** 

Hygiene measures

Storage class (LK) : LK 3 - Flammable liquids

## 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

# 8.1.1 National occupational exposure and biological limit values

Rustins Paint Driers (Terebene)		
Belgium - Occupational Exposure Limits		
Local name	Alcool n-butylique # n-Butanol	
OEL TWA	62 mg/m³	
	20 ppm	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference Koninklijk besluit/Arrêté royal 11/05/2021		
Croatia - Occupational Exposure Limits		
Local name	Butan-1-ol; n-butanol	
KGVI (OEL STEL)	154 mg/m³	
	50 ppm	
Remark	Koža (razvrstana kao tvar koja nadražuje kožu (H315))	
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)	
Germany - Occupational Exposure Limits (TRGS 900)		
Local name	Butan-1-ol	
AGW (OEL TWA)	310 mg/m³	

2/22/2024 (Revision date) EN (English) 5/16

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rustins Paint Driers (Terebene)	
	100 ppm
Peak exposure limitation factor	1(1)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Ireland - Occupational Exposure Limits	
Local name	Butan-1-ol [n-Butyl alcohol]
OEL TWA	20 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Romania - Occupational Exposure Limits	
Local name	n-Butanol
OEL TWA	100 mg/m³
	33 ppm
OEL STEL	200 mg/m³
	66 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovenia - Occupational Exposure Limits	
Local name	butan-1-ol
OEL TWA	310 mg/m³
	100 ppm
OEL STEL	310 mg/m³
	100 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	1-butanol
BLV	2 mg/g creatinine Parameter: 1-butanol (po hidrolizi) - Biološki vzorec: urin - Čas vzorčenja: pred delovno izmeno 10 mg/g creatinine Parameter: 1-butanol (po hidrolizi) - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	n-Butanol (Alcohol n-butílico)
VLA-ED (OEL TWA)	61 mg/m³
	20 ppm
VLA-EC (OEL STEL)	154 mg/m³
	50 ppm
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rustins Paint Driers (Terebene)		
North Macedonia - Occupational Exposure Limits		
Local name	Бутан-1-ол	
OEL TWA	310 mg/m³	
	100 ppm	
KTV	1	
Short time value [mg/m³]	310 mg/m³	
Short time value [ppm]	100 ppm	
Remark	(KTV) краткотрајна вредност (KTB) значи концентрација на опасни хемиски супстанци во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m3 или во ml/m3(ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (Y)	
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанци ("Службен весник на Република Македонија" бр.46/10)	
butan-1-ol; n-butanol (71-36-3)		
Ireland - Occupational Exposure Limits		
Local name	Butan-1-ol [n-Butyl alcohol]	
OEL TWA	20 ppm	
Regulatory reference	Chemical Agents Code of Practice 2021	
United Kingdom - Occupational Exposure Limits		
Local name	Butan-1-ol	
WEL STEL (OEL STEL)	154 mg/m³	
	50 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
	•	

## 8.1.2. Recommended monitoring procedures

No additional information available

## 8.1.3. Air contaminants formed

No additional information available

# 8.1.4. DNEL and PNEC

No additional information available

## 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2. Personal protection equipment

### Personal protective equipment:

Gloves. Dust/aerosol mask with filter type P1. Protective clothing.

## Personal protective equipment symbol(s):









#### 8.2.2.1. Eye and face protection

## Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

# Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

### 8.2.2.3. Respiratory protection

### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

#### 8.2.2.4. Thermal hazards

No additional information available

## 8.2.3. Environmental exposure controls

## Environmental exposure controls:

Avoid release to the environment.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Blue.

Odour : Aromatic hydrocarbon.

Odour threshold : Not available : No data available. Melting point Freezing point : Not available : 150 - 190 °C Boiling point Flammability : Not applicable : Not available Lower explosion limit Upper explosion limit : Not available : 38 °C Flash point

Auto-ignition temperature : No data available.

Decomposition temperature : Not available

pH : 7

Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available : Not available Density : 0.820 @ 20 C Relative density Relative vapour density at 20°C : No data available. Particle characteristics : Not applicable

2/22/2024 (Revision date) EN (English) 8/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

### 9.2.2. Other safety characteristics

No additional information available

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Flammable liquid and vapour.

## 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

Serious eye damage/irritation

Respiratory or skin sensitisation

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (innalation)	Not classified			
calcium bis(2-ethylhexanoate) (136-51-6)				
LD50 dermal rat > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermand Toxicity)				
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9: Naphtha (petroleum), hydrotreated heavy)				
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)			
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)			
Hydrocarbons, C9 - C11, n alkanes, isoalkane	es, cyclics, <2% aromatics (64742-48-9)			
LD50 oral rat	> 5000 mg/kg			
LD50 dermal rabbit	> 5000 mg/kg			
Skin corrosion/irritation :	Not classified pH: 7			

: May cause an allergic skin reaction.

: Causes serious eye damage.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germ cell mutagenicity : May cause genetic defects. Carcinogenicity : May cause cancer.

Reproductive toxicity : Suspected of damaging the unborn child. (if swallowed).

STOT-single exposure : May cause drowsiness or dizziness.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9: Naphtha (petroleum), hydrotreated heavy)

STOT-single exposure May cause drowsiness or dizziness.

butan-1-ol; n-butanol (71-36-3)

STOT-single exposure May cause drowsiness or dizziness. May cause respiratory irritation.

Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

calcium bis(2-ethylhexanoate) (136-51-6)

180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other: NOAEL (subchronic, oral, animal/male, 90 days)

NOAEL (subchronic, oral, animal/female, 90 days) 205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:

Aspiration hazard Not classified

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9: Naphtha (petroleum), hydrotreated heavy)

Viscosity, kinematic 1.8 mm<sup>2</sup>/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm<sup>2</sup>/s)'

#### 11.2. Information on other hazards

No additional information available

## **SECTION 12: Ecological information**

## 12.1. Toxicity

: Harmful to aquatic life with long lasting effects. Ecology - general

Hazardous to the aquatic environment, short-term : Not classified

Hazardous to the aquatic environment, long-term

: Not classified

(chronic)

calcium bis(2-ethylhexanoate) (136-51-6)		
LC50 - Fish [1] > 100 mg/l Test organisms (species): Oryzias latipes		
EC50 - Crustacea [1]	910 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	49.3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	

## 12.2. Persistence and degradability

Rustins Paint Driers (Terebene)		
Persistence and degradability Not rapidly degradable		
COBALT 6 % (13586-82-8)		
Persistence and degradability  Not rapidly degradable		

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

calcium	bis(2-ethyl	hexanoate)	(136-51-6)
---------	-------------	------------	------------

Persistence and degradability Not rapidly degradable

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9: Naphtha (petroleum), hydrotreated heavy)

Persistence and degradability Not rapidly degradable

butan-1-ol; n-butanol (71-36-3)

Persistence and degradability Not rapidly degradable

Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

Persistence and degradability Not rapidly degradable

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] (64742-95-6)

Persistence and degradability Not rapidly degradable

### 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

# 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Additional information

: Flammable vapours may accumulate in the container.

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263	
14.2. UN proper shippin	14.2. UN proper shipping name				
PAINT / PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
	-	IAIA	ASIT	1115
Transport document descr	ription			
UN 1263 PAINT / PAINT	UN 1263 PAINT RELATED	UN 1263 Paint related	UN 1263 PAINT RELATED	UN 1263 PAINT RELATED
RELATED MATERIAL, 3, III, (D/E)	MATERIAL, 3, III	material, 3, III	MATERIAL, 3, III	MATERIAL, 3, III
14.3. Transport hazard	class(es)			
3	3	3	3	3
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental haz	zards			
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the
environment: No	environment: No Marine pollutant: No	environment: No	environment: No	environment: No
No supplementary information	on available			

### 14.6. Special precautions for user

## **Overland transport**

Classification code (ADR) : F1

Special provisions (ADR) : 163, 367, 650

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30

Orange plates : In the state of the state of

30 1263

Tunnel restriction code (ADR) : D/E EAC code : •3Y

### Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : P001, LP01 Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T2 Tank special provisions (IMDG) : TP1, TP29 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Stowage category (IMDG) : A

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

#### Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

#### **Inland waterway transport**

Classification code (ADN) : F1

Special provisions (ADN) : 163, 367, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

#### Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 650

Limited quantities (RID) : 5L Excepted quantities (RID) : E1 : P001, R001 Packing instructions (RID) : PP1 Special packing provisions (RID) Mixed packing provisions (RID) : MP19 Transport category (RID) : 3 : CE4 Colis express (express parcels) (RID) Hazard identification number (RID) : 33

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

## **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

## **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

# **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

## **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

### **France**

Occupational diseases		
Code	Description	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany	
Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG).  Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Chemicals Prohibition Ordinance (ChemVerbotsV)	: This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).
Hazardous Incident Ordinance (12. BlmSchV)	: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)
Netherlands	
ABM category	: Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioacumulative potential/ toxicity or persistence)
SZW-lijst van kankerverwekkende stoffen	: Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed
SZW-lijst van mutagene stoffen	: Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed
Denmark	

#### **Denmark**

Class for fire hazard : Class II-1 Store unit : 5 liter

Classification remarks : R10 <H226;H317;H318;H336;H340;H350;H361>; Emergency management guidelines for

the storage of flammable liquids must be followed

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

The requirements from the Danish Working Environment Authorities regarding work with

carcinogens must be followed during use and disposal

#### **Switzerland**

Chemicals Ordinance (ChemV, SR 813.11) : Group 1

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH	Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
Carc. 1B	Carcinogenicity, Category 1B		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H226	Flammable liquid and vapour.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H340	May cause genetic defects.		
H350	May cause cancer.		
H361	Suspected of damaging fertility or the unborn child.		
H361f	Suspected of damaging fertility.		
H412	Harmful to aquatic life with long lasting effects.		
Muta. 1B	Germ cell mutagenicity, Category 1B		
Repr. 2	Reproductive toxicity, Category 2		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1	Skin sensitisation, Category 1		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.