# Safety Data Sheet according to Regulation (EC) No. 2015/830 Petrol Treatment

Revision date: 06/07/2020

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product name: Silverhook Petrol Treatment

ref: SGA01

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Fuel Additive

## 1.3 Details of the supplier of the safety data sheet

**Supplier** 

Silverhook Ltd Unit 14 Bates Road

Harold Wood, London, England

RM3 0JH

Tel.: +44 (0) 1708330500 Fax.: +44 (0) 1708330504 Email: <u>522@silverhook.co.uk</u>

Responsible person email: 522@silverhook.co.uk

## 1.4 Emergency Telephone Number

+44 (0)1708330500 (during office hours)

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1 Classification of the substance or mixture

## Classification according to Directive 67/548/EEC or 1999/45/EC

Harmful: may cause lung damage if swallowed.

Xn; R 65 · R 66

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

## Hazard pictograms



Health hazard (GHS08)

May be fatal if swallowed and enters airways.

## Signal word

Danger

# **Hazard Statements**

## **Precautionary statements**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations

#### Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

## 2.3 Other hazards

None

Page: 1/6

# Safety Data Sheet according to Regulation (EC) No. 2015/830 Petrol Treatment

Revision date: 06/07/2020

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures

## **Hazardous ingredients**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE - UNSPECIFIED ; EC No : 265-149-8; CAS No. : 64742-47-8.

 Weight fraction:
 50 - 100 %

 Classification 67/548/EEC:
 Xn; R65

 Classification 1272/2008 [CLP]:
 Asp.Tox. 1; H304

HYDROCARBONS,C10-13,n-ALKANES, <2% AROMATIC; REACH registration No: n/a; EC No: 918-481-9; CAS No.:

 Weight fraction:
 2 - 3 %

 Classification 67/548/EEC:
 Xn; R65 R66

 Classification 1272/2008 [CLP]:
 Asp.Tox. 1; H304

PHENOL (DIMETHYLAMINO)METHYLPOLYISOBUTYLENE DERIVIATIVES EC No POLYMER

Weight fraction : 1.5 - 3%Classification 67/548/EEC : Xn; R52/53

Classification 1272/2008 [CLP]: Aquatic Chronic 3; H412

HYDROCARBONS, C10, AROMATICS; EC No: 919-284-0-8

Weight fraction: < 1 %

Classification 67/548/EEC: N; R51/53 Xn; R65 R67 R66

Classification 1272/2008 [CLP]: Asp.Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411

**Additional information** 

Full text of R-, H- and EUH-phrases: see section 16.

## **SECTION 4: FIRST-AID MEASURES**

#### 4.1 Description of first aid measures

#### **General information**

Medical treatment necessary.

#### After inhalation

No special measures are necessary.

# In case of skin contact

After cleaning apply high-fat content skin care cream.

## After eye contact

No special measures are necessary.

## After ingestion

Rinse mouth thoroughly with water. Give nothing to eat or drink. Do not induce vomiting. Call a physician in any case!

## 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions Respiratory complaints.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Observe risk of aspiration if vomiting occurs.

# **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

## Suitable extinguishing media

Alcohol resistant foam. Carbon dioxide (CO2). Extinguishing powder. Water mist

Page: 2 / 6



# Safety Data Sheet according to Regulation (EC) No. 2015/830 Petrol Treatment

Revision date: 06/07/2020

## Unsuitable extinguishing media

Strong water jet.

#### 5.2 Special hazards arising from the substance or mixture

#### **Hazardous combustion products**

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide. Nitrogen oxides (NOx)

#### 5.3 Advice for firefighters

Do not inhale explosion and combustion gases. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

## Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1 Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8.

#### 6.2 Environmental precautions

Ensure all waste water is collected and treated via a waste water treatment plant. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Suitable material for taking up: Sand. Kieselguhr. Universal binder Sawdust. Collect in closed and suitable containers for disposal.

#### 6.4 Reference to other sections

See protective measures under point 7 and 8.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1 Precautions for safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. When using do not eat, drink, smoke or sniff. Wash hands before breaks and after work. All work processes must always be designed so that the following is as low as possible: Eye contact, skin contact, inhalation of vapours or spray/mists. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Wear personal protection equipment. (see chapter 8).

## 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Keep the packing dry and well-sealed to prevent contamination and absorption of humidity. Never use pressure to empty container.

## Hints on storage assembly

Keep away from: Oxidising agent Acid. Alkali **Storage class:** 10

## 7.3 Specific end uses

None

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1 Control parameters

None

## **8.2 Exposure controls**

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

# Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## Personal protective equipment

## Eye / face protection

Eye glasses with side protection

Skin protection





Page: 3 / 6

# Safety Data Sheet according to Regulation (EC) No. 2015/830 Petrol Treatment

Revision date: 06/07/2020

#### Hand protection

Gloves with long cuffs. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Breakthrough times and swelling properties of the material must be taken into consideration.

#### **Body protection**

Overall.

#### Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient exhaust Handling larger quantities. Container device with compressed air (DIN EN 137). / Filtering device (full mask or mouthpiece) with filter: Filter types:A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m3 (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m3 (1.0 % by vol.)

#### **Environmental exposure controls**

Send to a hazardous waste incinerator facility under observation of official regulations.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1 Information on basic physical and chemical properties

## Safety relevant basis data

Physical state: Liquid

Odour : Characteristic Hydrocarbon

Colour: Light Brown
Boiling temperature / boiling range@ 760mmHg/°C: 200 - 250
Flash point (PMcc)/°C: > 75
Vapour pressure@50°C < 1000 hPa
Density @15°C/ g/cm³: 0.80
Water solubility @20°C: Insoluble
Viscosity@ 40°C / mm2/s: < 7.5

9.2 Other information

pH value  $\,$  N/A Ethanol content % 0

# **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No information available.

#### 10.2 Chemical stability

No information available.

# 10.3 Possibility of hazardous reactions

No information available.

## 10.4 Conditions to avoid

No information available.

## 10.5 Incompatible materials

Exothermic reaction with: Oxidising agent. Strong acid Strong alkali

# 10.6 Hazardous decomposition products

Decomposition with: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide. Nitrogen oxides (NO<sub>x</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

This mixture is classified as dangerous according to 1999/45/EC. This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP]. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

# 11.1 Information on toxicological effects

Harmful: may cause lung damage if swallowed. For viscosity data, see chapter 9. Repeated exposure may cause skin dryness or cracking. Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

## Acute effects

**Acute oral toxicity** 

Parameter: LD50 (ALKANES, C10-14-ISO-; EC No: 918-481-9)

Page: 4/6

# Safety Data Sheet according to Regulation (EC) No. 2015/830 Petrol Treatment

Revision date: 06/07/2020

Exposure route: Oral

Effective dose: > 10000 mg/kg

Acute dermal toxicity

Parameter: LD50 ( ALKANES, C10-13-ISO- ; EC No : 918-481-9)

Exposure route: Dermal
Effective dose: > 3160 mg/kg

Acute inhalation toxicity

Parameter: LC50 ( SOLVENT NAPHTA (PETROLEUM), HEAVY AROMATIC ; CAS No. : 64742-94-5

) Exposure route : Inhalation
Species : Rat
Effective dose : > 590 mg/m³
Exposure time : 4 h

# **SECTION 12: ECOLOGICAL INFORMATION**

## 12.1 Toxicity

#### **Aquatic toxicity**

Harmless to aquatic organisms up to the tested concentration

Acute (short-term) algae toxicity

Parameter: EC50 (SOLVENT NAPHTA (PETROLEUM), HEAVY AROMATIC; CAS No.: 64742-94-5)

Species: Algae
Effective dose: 1 - 3 mg/l
Exposure time: 72 h

Parameter: EC50 (SOLVENT NAPHTA (PETROLEUM), HEAVY AROMATIC; CAS No.: 64742-94-5)

Species: Daphnia
Effective dose: 3 - 10 mg/l
Exposure time: 48 h

## 12.2 Persistence and degradability

No information available.

## 12.3 Bioaccumulative potential

No information available.

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII

## 12.6 Other adverse effects

The evaluation was carried out according to the calculation method of the preparation directive.

# 12.7 Further ecological information

None

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

Send to a hazardous waste incinerator facility under observation of official regulations. Clean IBCs or drums at approved facility only. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: TRANSPORT INFORMATION**

## 14.1 UN number

No dangerous good in sense of this transport regulation.

# 14.2 UN proper shipping name

No dangerous good in sense of this transport regulation.

#### 14.3 Transport hazard class(es)

Land transport (ADR/RID)

5//

# Safety Data Sheet according to Regulation (EC) No. 2015/830

**Petrol Treatment** 

Revision date: 26/07/2018

Not subject to ADR/RID.

Class(es):

Sea transport (IMDG)

Not subject to IMDG code.

Class(es):

Air transport (ICAO-TI / IATA-DGR)

Not subject to IATA regulations.

Class(es):

## 14.4 Packing group

No dangerous good in sense of this transport regulation.

#### 14.5 Environmental hazards

No dangerous good in sense of this transport regulation.

#### 14.6 Special precautions for user

None

#### 14.7 Transport in bulk

according to Annex II of MARPOL and the IBC Code: N/A

## **SECTION 15: REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** 

**Technische Anleitung Luft (TA-Luft)** 

Weight fraction (Number 5.2.5. I): < 5 %

Water hazard class (WGK)

Class: 2 (Hazardous to water) Classification according to VwVwS

#### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: OTHER INFORMATION**

## 16.1 Indication of changes

03. Hazardous ingredients

#### 16.2 Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data

None

## 16.5 Relevant R-, H- and EUH-phrases (Number and full text)

| H304 | May be fatal if swallowed and enters |
|------|--------------------------------------|
| H336 | airways. May cause drowsiness or     |

H373 dizziness.

H411 May cause damage to organs through prolonged or repeated exposure.

H412 Toxic to aquatic life with long lasting effects.
H413 Harmful to aquatic life with long lasting effect

48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

May cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

## 16.6 Training advice

None

# 16.7 Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.