

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML
- **Article number:** 433.0010599.076
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Paint remover
- **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
European Aerosols B.V.
Wolfraamweg 2
NL-8471 XC Wolvega
The Netherlands
Tel : +31 (0)561 694400
e-mail: sds-nl@european-aerosols.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**
+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML**

(Contd. of page 1)

· **2.2 Label elements**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**

GHS02 GHS05 GHS07

· **Signal word** Danger· **Hazard-determining components of labelling:**

propan-1-ol

acetone

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700-1000)

iso-butanol

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients**· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 67-64-1	acetone	20-<25%
EINECS: 200-662-2	Flam. Liq. 2, H225	
Index number: 606-001-00-8	Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119471330-49	EUH066	

(Contd. on page 3)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 2)

CAS: 71-23-8 EINECS: 200-746-9 Index number: 603-003-00-0 Reg.nr.: 01-211948-6761-29-xxxx	propan-1-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Dam. 1, H318 ⚠ STOT SE 3, H336	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23	iso-butanol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	2.5-<5%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700-1000) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-<5%
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32-0032	Carbon black substance with a Community workplace exposure limit	2.5-<5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	2.5-<5%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 3)

- Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML**

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

71-23-8 propan-1-ol

WEL Short-term value: 625 mg/m³, 250 ppm
Long-term value: 500 mg/m³, 200 ppm
Sk

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

78-83-1 iso-butanol

WEL Short-term value: 231 mg/m³, 75 ppm
Long-term value: 154 mg/m³, 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

1333-86-4 Carbon black

WEL Short-term value: 7 mg/m³
Long-term value: 3.5 mg/m³

13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³
*total inhalable **respirable

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Sk

· DNELs

67-64-1 acetone

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m ³ (Worker, acute local)
	DNEL	1210 mg/m ³ (Worker, longterm systemic)
	DNEL	200 mg/m ³ (Consumer, longterm systemic)
	DNEL	60 mg/m ³

108-65-6 2-methoxy-1-methylethyl acetate

Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)
	DNEL	320 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	275 mg/m ³ (Worker, longterm systemic)

(Contd. on page 6)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 5)

	DNEL	33 mg/m ³ (Consumer, longterm systemic)
107-98-2 1-methoxy-2-propanol		
Oral	DNEL	3.3 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	50.6 mg/kg /per day (Worker, longterm systemic)
	DNEL	18.1 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	553.5 mg/m ³ (Worker, acute local)
	DNEL	369 mg/m ³ (Worker, longterm systemic)
	DNEL	43.9 mg/m ³ (Consumer, longterm systemic)

· **PNECs**

67-64-1 acetone

PNEC	10.6 mg/l (Freshwater)
PNEC	1.06 mg/l (Seawater)
PNEC	21 mg/l (Sporadic release)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	30.4 mg/kg (Freshwater sediment)
PNEC	3.04 mg/kg (Seawater sediment)
PNEC	29.5 mg/kg (Soil)

108-65-6 2-methoxy-1-methylethyl acetate

PNEC	0.635 mg/l (Freshwater)
PNEC	0.064 mg/l (Seawater)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	3.29 mg/kg (Freshwater sediment)
PNEC	0.329 mg/kg (Seawater sediment)
PNEC	0.29 mg/kg (Soil)

107-98-2 1-methoxy-2-propanol

PNEC	10 mg/l (Freshwater)
PNEC	1 mg/l (Seawater)
PNEC	100 mg/l (Sporadic release)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	52.3 mg/kg (Freshwater sediment)
PNEC	5.2 mg/kg (Seawater sediment)
PNEC	4.59 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Avoid contact with the eyes.
- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML**

(Contd. of page 6)

Filter A2/P3

- **Hand protection**



Protective gloves

- **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

- **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Aerosol

- **Colour:**

Silver-coloured

- **Odour:**

Solvent-like

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

- **Flammability**

Not applicable.

- **Lower and upper explosion limit**

- **Lower:**

1.2 Vol %

- **Upper:**

13 Vol %

- **Flash point:**

Not applicable, as aerosol.

- **Auto-ignition temperature:**

240 °C (464 °F)

- **Decomposition temperature:**

Not determined.

- **pH**

Not determined.

- **Viscosity:**

- **Kinematic viscosity**

Not determined.

- **Dynamic:**

Not determined.

- **Solubility**

- **water:**

Not miscible or difficult to mix.

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Vapour pressure at 20 °C (68 °F):**

4000 hPa (3000.2 mm Hg)

- **Density and/or relative density**

- **Density at 20 °C (68 °F):**

0.8 g/cm³ (6.7 lbs/gal)

- **Relative density**

Not determined.

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 7)

· **Vapour density** Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Aerosol

· **Important information on protection of health and environment, and on safety.**

· **Explosive properties:**

Not determined.

· **Solvent content:**

· **Organic solvents:**

83.9 %

· **VOC (EC)**

666.1 g/l

· **VOC-EU%**

83.89 %

· **Solids content:**

3.0 %

· **Change in condition**

· **Evaporation rate**

Not applicable.

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

· **Aerosols**

Extremely flammable aerosol. Pressurised container:
May burst if heated.

· **Oxidising gases**

Void

· **Gases under pressure**

Void

· **Flammable liquids**

Void

· **Flammable solids**

Void

· **Self-reactive substances and mixtures**

Void

· **Pyrophoric liquids**

Void

· **Pyrophoric solids**

Void

· **Self-heating substances and mixtures**

Void

· **Substances and mixtures, which emit flammable gases in contact with water**

Void

· **Oxidising liquids**

Void

· **Oxidising solids**

Void

· **Organic peroxides**

Void

· **Corrosive to metals**

Void

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
------	------	------------------

(Contd. on page 9)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 8)

Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)
<ul style="list-style-type: none"> · Skin corrosion/irritation No irritant effect. · Serious eye damage/irritation Causes serious eye damage. · Respiratory or skin sensitisation May cause an allergic skin reaction. · STOT-single exposure May cause drowsiness or dizziness. 		
<ul style="list-style-type: none"> · 11.2 Information on other hazards 		
<ul style="list-style-type: none"> · Endocrine disrupting properties 		
None of the ingredients is listed.		

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-64-1 acetone

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

GB

(Contd. on page 10)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022



Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 9)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.
- **Label** 2.1
- **IMDG, IATA**
- 
- **Class** 2.1 Gases.
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** not regulated
- **14.5 Environmental hazards:** Not applicable.
- **14.6 Special precautions for user** Warning: Gases.
- **Hazard identification number (Kemler code):** -
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:

(Contd. on page 11)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 10)

·	Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

* **SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

67-64-1	acetone	Listed
---------	---------	--------

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

(Contd. on page 12)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 33 (replaces version 32)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 10599 ZINC PRIMER 6UC 400 ML

(Contd. of page 11)

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

• **Classification according to Regulation (EC) No 1272/2008**

Data is based on internal technical data and technical data from suppliers.

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**

GB