

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML
- **Article number:** 433.0009432.076
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Paint remover
- **Process category**  
PROC7 Industrial spraying  
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
European Aerosols B.V.  
Wolfraamweg 2  
NL-8471 XC Wolvega  
The Netherlands  
Tel : +31 (0)561 694400  
e-mail: sds-nl@european-aerosols.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**  
+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2                      H315                      Causes skin irritation.  
Eye Irrit. 2                      H319                      Causes serious eye irritation.  
STOT SE 3                      H336                      May cause drowsiness or dizziness.  
Aquatic Chronic 3                      H412                      Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Danger· **Hazard-determining components of labelling:**

acetone

Hydrocarbons, C9, aromatics

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.\* **SECTION 3: Composition/information on ingredients**· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ----- ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	50-<75%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ----- ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	12.5-<20%

(Contd. on page 3)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31













Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 2)

EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene  Flam. Liq. 3, H226  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H335-H336 EUH066	5-<10%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol  Acute Tox. 3, H331  Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene  Flam. Liq. 2, H225  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332 Aquatic Chronic 3, H412	<2.5%

• **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.

(Contd. on page 4)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 3)

- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
-----	---

#### 67-64-1 acetone

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	--

#### xylene

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

#### 111-76-2 2-butoxyethanol

WEL	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 123 mg/m <sup>3</sup> , 25 ppm Sk, BMGV
-----	---

#### 100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

(Contd. on page 5)

GB

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 4)

<b>· DNELs</b>		
<b>67-64-1 acetone</b>		
Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	1210 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	200 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	60 mg/m <sup>3</sup>
<b>xylene</b>		
Oral	DNEL	1.6 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	180 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	211 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	221 mg/m <sup>3</sup> (Worker, longterm local)
	DNEL	442 mg/m <sup>3</sup> (Worker, acute systemic)
	DNEL	289 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	14.8 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	260 mg/m <sup>3</sup> (Consumer; acute systemic)
	DNEL	65.3 mg/m <sup>3</sup> (Consumer, longterm local)
	DNEL	260 mg/m <sup>3</sup> (Consumer, acute local)
<b>Hydrocarbons, C9, aromatics</b>		
Oral	DNEL	11 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	25 mg/kg /per day (Worker, longterm systemic)
	DNEL	11 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	150 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	32 mg/m <sup>3</sup> (Consumer, longterm systemic)
<b>111-76-2 2-butoxyethanol</b>		
Oral	DNEL	3.2 mg/kg (Consumer, longterm systemic)
	DNEL	13.4 mg/kg (Consumer, acute systemic)
Dermal	DNEL	75 mg/kg /per day (Worker, longterm systemic)
	DNEL	89 mg/kg /per day (Worker, acute systemic)
	DNEL	38 mg/kg (Consumer, longterm systemic)
Inhalative	DNEL	44.5 mg/kg /per day (Consumer, acute systemic)
	DNEL	98 mg/m <sup>3</sup> /20 ppm (Worker, longterm systemic)
	DNEL	663 mg/m <sup>3</sup> /135 ppm (Worker, acute systemic)
	DNEL	246 mg/m <sup>3</sup> /50 ppm (Worker, acute local)
	DNEL	49 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	426 mg/m <sup>3</sup> (Consumer; acute systemic)
DNEL	123 mg/m <sup>3</sup> (Consumer, acute local)	
<b>· PNECs</b>		
<b>67-64-1 acetone</b>		
PNEC	10.6 mg/l (Freshwater)	
PNEC	1.06 mg/l (Seawater)	
PNEC	21 mg/l (Sporadic release)	
PNEC	100 mg/l (Sewage treatment plant)	

(Contd. on page 6)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 5)

PNEC	30.4 mg/kg (Freshwater sediment)
PNEC	3.04 mg/kg (Seawater sediment)
PNEC	29.5 mg/kg (Soil)

**111-76-2 2-butoxyethanol**

PNEC	8.8 mg/l (Freshwater)
PNEC	0.88 mg/l (Seawater)
PNEC	9.1 mg/l (Sporadic release)
PNEC	463 mg/l (Sewage treatment plant)
PNEC	34.6 mg/kg (Freshwater sediment)
PNEC	3.45 mg/kg (Seawater sediment)
PNEC	2.8 mg/kg (Soil)

**· Ingredients with biological limit values:****xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

**111-76-2 2-butoxyethanol**

BMGV	240 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: butoxyacetic acid

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

**· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

**· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

**· Hand protection**

Protective gloves

**· Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

**· Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 6)

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

Colourless

· **Odour:**

Solvent-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

2.6 Vol % (67-64-1 acetone)

· **Upper:**

26.2 Vol % (115-10-6 dimethyl ether)

· **Flash point:**

Not applicable, as aerosol.

· **Auto-ignition temperature:**

240 °C (464 °F)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C (68 °F):**

4000 hPa (3000.2 mm Hg)

· **Density and/or relative density**

· **Density at 20 °C (68 °F):**

0.8 g/cm<sup>3</sup> (6.7 lbs/gal)

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Aerosol

· **Important information on protection of health and environment, and on safety.**

· **Explosive properties:**

Not determined.

· **Solvent content:**

· **Organic solvents:**

87.5 %

· **VOC (EC)**

---

668.5 g/l

· **VOC-EU%**

87.50 %

· **Solids content:**

12.4 %

(Contd. on page 8)

GB

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML

(Contd. of page 7)

· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

<b>67-64-1 acetone</b>		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)
<b>xylene</b>		
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m <sup>3</sup> (rat)
<b>Hydrocarbons, C9, aromatics</b>		
Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rab) (OECD 402)

(Contd. on page 9)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 8)

**111-76-2 2-butoxyethanol**

Oral	LD50	1200 mg/kg (guinea pig)
Inhalative	LC50 / 4 h	3 mg/m <sup>3</sup> (rat)
	LC50 / 96 h	>100 mg/l (oncorhynchus mykiss) (Oncorhynchus mykiss)

**100-41-4 ethylbenzene**

Oral	LD50	3500 mg/kg (rat)
------	------	------------------

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****115-10-6 dimethyl ether**

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

**67-64-1 acetone**

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

**xylene**

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

**Hydrocarbons, C9, aromatics**

EC50 / 48 h	302 mg/l (daphnia magna)
EC50 / 72 h	2.75 mg/l (Pseudokirchneriella subcapitata)
EC50 / 96 h	9.2 mg/l (Regenbogenforelle)

**111-76-2 2-butoxyethanol**

LC50 / 48 h	1550 mg/l (daphnia magna)
LC50 / 72 h	1840 mg/l (Pseudokirchneriella subcapitata)
LC50 / 96 h	1474 mg/l (Regenbogenforelle)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish

(Contd. on page 10)

GB

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 9)

· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:**

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

**SECTION 14: Transport information**· **14.1 UN number or ID number**· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG, IATA**· **Class**

2.1 Gases.

· **Label**

2.1

· **14.4 Packing group**· **ADR, IMDG, IATA**

not regulated

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):**

-

· **EMS Number:**

F-D,S-U

(Contd. on page 11)

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 10)

· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

67-64-1 acetone

Listed

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 12)

GB

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.05.2024

Version number 3 (replaces version 2)

Revision: 30.03.2022

**Trade name: PLASTI-KOTE 9432 STONE CLEAR SEALER 6UC 400 ML**

(Contd. of page 11)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Data is based on internal technical data and technical data from suppliers.

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - VOC: Volatile Organic Compounds (USA, EU)
  - DNEL: Derived No-Effect Level (UK REACH)
  - PNEC: Predicted No-Effect Concentration (UK REACH)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Flam. Gas 1A: Flammable gases – Category 1A
  - Aerosol 1: Aerosols – Category 1
  - Press. Gas (Comp.): Gases under pressure – Compressed gas
  - Flam. Liq. 2: Flammable liquids – Category 2
  - Flam. Liq. 3: Flammable liquids – Category 3
  - Acute Tox. 4: Acute toxicity – Category 4
  - Acute Tox. 3: Acute toxicity – Category 3
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
  - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
  - Asp. Tox. 1: Aspiration hazard – Category 1
  - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
  - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- **\* Data compared to the previous version altered.**