

Declaration of Performance

Document number: (1015-CPR-30-10956/1-6)

Product Identification:	ForgeFast woodscrew <ul style="list-style-type: none">• Head: double flat• Recess: Torx, Pozi• Full/Partial thread• Material: 10B21
Intended Use of the Product:	ForgeFast woodscrews can be used in load-bearing structural timber products
Manufacturer:	Forgefix Ltd Botany Business Park Macclesfield Road Whaley Bridge High Peak SK23 7DQ
System of AVCP:	Scheme type 1A
Notified Body:	Name: Strojirensky zkusebni ustav, s.p. Notified Body Number: 1015
Harmonised Standards:	EN14592:2008+A1:2012

The performance of the mentioned products is in conformity with the declared performance given below:

ForgeFast Woodscrew 3.0mm

Product	Characteristic yield moment My,k [Nmm]	Characteristic withdrawal parameter fax,k [N/mm ²]		Characteristic head pull-through parameter fhead,k [N/mm ²]	Characteristic tensile capacity ftens,k [kN]	Characteristic torsional ratio
		Loading across the fibre	Loading along the fibre			
	-			-	-	-
Woodscrew 3.0mm	1 401	19,86	13,81	27,75	2,02	2,39
Characteristic density of wood Pk [kg/m ³]	-	35°		35°	-	45°
Durability (corrosion protection)	Cr3+, yellow/zinc plated, nano high corrosion resistance, min. 3 um (Service Class 1 acc. To EN 1995-1-1)					

ForgeFast Woodscrew 3.5mm

Product	Characteristic yield moment My,k [Nmm]	Characteristic withdrawal parameter fax,k [N/mm ²]		Characteristic head pull-through parameter fhead,k [N/mm ²]	Characteristic tensile capacity ftens,k [kN]	Characteristic torsional ratio
		Loading across the fibre	Loading along the fibre			
	-			-	-	-
Woodscrew 3.5mm	2 246	18,66	13,24	25,61	4,75	2,20
Characteristic density of wood Pk [kg/m ³]	-	35°		35°	-	45°
Durability (corrosion protection)	Cr3+, yellow/zinc plated, nano high corrosion resistance, min. 3 um (Service Class 1 and 2 acc. To EN 1995-1-1)					

ForgeFast Woodscrew 4.0mm

Product	Characteristic yield moment My,k [Nmm]		Characteristic withdrawal parameter fax,k [N/mm ²]		Characteristic head pull-through parameter fhead,k [N/mm ²]		Characteristic tensile capacity ftens,k [kN]	Characteristic torsional ratio
			Loading across the fibre	Loading along the fibre				
	-				-		-	-
Woodscrew 4.0mm	3 490		19,01	13,39	24,85		6,31	3,17
Characteristic density of wood Pk [kg/m ³]	-		350		350		-	450
Durability (corrosion protection)	Cr3+, yellow/zinc plated, nano high corrosion resistance, min. 3 um (Service Class 1 acc. To EN 1995-1-1)							

ForgeFast Woodscrew 4.5mm

Product	Characteristic yield moment My,k [Nmm]		Characteristic withdrawal parameter fax,k [N/mm ²]		Characteristic head pull-through parameter fhead,k [N/mm ²]		Characteristic tensile capacity ftens,k [kN]	Characteristic torsional ratio
	Thread section	Smooth section	Loading across the fibre	Loading along the fibre	Double flat head	Trim head		
							-	-
Woodscrew 4.5mm	5 627	9 235	19,86	14,31	24,47	28,52	8,52	3,07
Characteristic density of wood Pk [kg/m ³]	-		350		350		-	450
Durability (corrosion protection)	Cr3+, yellow/zinc plated, nano high corrosion resistance, min. 3 um (Service Class 1 and 2 acc. To EN 1995-1-1)							

ForgeFast Woodscrew 5.0mm

Product	Characteristic yield moment My,k [Nmm]		Characteristic withdrawal parameter fax,k [N/mm ²]		Characteristic head pull-through parameter fhead,k [N/mm ²]	Characteristic tensile capacity ftens,k [kN]	Characteristic torsional ratio
	Thread section	Smooth section	Loading across the fibre	Loading along the fibre	-	-	-
Woodscrew 5.0mm	7 103	12 274	19,32	14,39	2402	10,10	3,06
Characteristic density of wood Pk [kg/m ³]	-		35°		35°	-	45°
Durability (corrosion protection)	Cr ₃ +, yellow/zinc plated, nano high corrosion resistance, min. 3 µm (Service Class 1 and 2 acc. To EN 1995-1-1)						

ForgeFast Woodscrew 6.0mm

Product	Characteristic yield moment My,k [Nmm]	Characteristic withdrawal parameter fax,k [N/mm ²]		Characteristic head pull-through parameter fhead,k [N/mm ²]	Characteristic tensile capacity ftens,k [kN]	Characteristic torsional ratio	
	-	Loading across the fibre	Loading along the fibre	-	-	-	
Woodscrew 6.0mm	10 575	17,01	12,55	24,59	13,10	4,11	
Characteristic density of wood Pk [kg/m ³]	-		35°		35°	-	45°
Durability (corrosion protection)	Cr ₃ +, yellow/zinc plated, nano high corrosion resistance, min. 3 µm (Service Class 1 and 2 acc. To EN 1995-1-1)						

Forgefix Ltd
Botany Business Park
Macclesfield Road
Whaley Bridge
SK23 7DQ



The performance of the product identified above is in conformity with the set of declared performances. This declaration is issued in accordance with Regulation (EU) No 305/2011. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of:	Forgefix Ltd
Place of issue:	Botany Business Park, Macclesfield Road, Whaley Bridge, SK23 7DQ
Date of issue:	02/01/2019
Name:	Anthony Armit
Position:	Commercial Director
Signature:	
Date:	04/01/2019