

Declaration of Performance

No: DOP-G130

Unique identification code of the product-type:	G130 – The Works Pro Clear
Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Sealant for non-structural façade interior applications EN 15651-1: F INT
Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11(5):	Sherwin-Williams UK Limited, Thorncliffe Park, Chapeltown, Sheffield, S35 2YP
System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	System 3
In case of the declaration of performance concerning a construction product covered by a harmonised standard:	Notified Body No: 1023 – Institute for Testing and Certification (ITC) performed Initial-type testing under system 3 and issued a test report against the requirements for: Sealant intended for Non-structural Façade Interior applications EN 15651-1 (2012)

Declared performance (EN 15651-1:2012)

Characteristic	Declared Performance
Reaction to fire (EN ISO 11925-2)	NPD
Release of chemicals dangerous to the environment and health	See product safety data sheet (MSDS)
Water Tightness and Air Tightness - Resistance to Flow (ISO 7390)	≤5mm
Water Tightness and Air Tightness - Loss of Volume (ISO 10563)	≤45%
Water Tightness and Air Tightness - Elongation at break at (23°C) (EN ISO 8339)	≥25%
Durability	No Failure (NF)

Conditioning: **Method B** Test substrate(s): **Aluminum (no primer)**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Katherine Brown
Technical Manager (R&D)At Sheffield (UK) on 21st November 2022

Declaration of Performance

No: DOP-G130UK

Unique identification code of the product-type:	G130-UK – The Works Pro Clear
Intended use/es:	Sealant for non-structural façade interior applications (F INT)
Manufacturer:	Sherwin-Williams UK Limited, Thorncliffe Park, Chapeltown, Sheffield, S35 2YP
System/s of AVCP:	System 3
Designated Standard:	Sealant intended for Non-structural Facade Interior applications EN 15651-1 (2012)
Approved Body:	2538 - 4ward Testing Ltd

Declared performance:

Characteristic	Declared Performance
Reaction to fire (EN ISO 11925-2)	NPD
Release of chemicals dangerous to the environment and health	See product safety data sheet (MSDS)
Water Tightness and Air Tightness - Resistance to Flow (ISO 7390)	≤5mm
Water Tightness and Air Tightness - Loss of Volume (ISO 10563)	≤45%
Water Tightness and Air Tightness - Elongation at break at (23°C) (EN ISO 8339)	≥25%
Durability	No Failure (NF)

Conditioning: **Method B** Test substrate: **Aluminium (no primer)**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Katherine Brown
Technical Manager (R&D)

At Sheffield (UK) on 21st November 2022

