

Declaration of Performance

No: DOP-G129

Unique identification code of the product-type:

G129 – The Works Pro

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for non-structural façade interior and exterior applications EN 15651-1: F EXT-INT and Non-structural Sanitary applications EN15651-3: XS and Non-structural Pedestrian Walkway Interior applications EN15651-4: PW-INT

Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11(5):

Sherwin-Williams UK Limited, Thorncliffe Park, Chapeltown, Sheffield, S35 2YP

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified Body No: 1023 – Institute for Testing and Certification (ITC) performed Initial-type testing under system 3 and issued a test report against the requirements for: Sealant intended for Non-structural Facade Exterior-Interior applications EN 15651-1 (2012) and Non-structural Sanitary applications EN15651-3 (2012) and Non-structural Pedestrian Walkway Interior applications EN15651-4 (2012)

Declared performance

Characteristic	Declared Performance	Harmonised Standard
Reaction to fire (EN ISO 11925-2)	NPD	EN 15651 Parts 1 & 3 & 4 (2012)
Release of chemicals dangerous to the environment and health	See product safety data sheet (SDS)	EN 15651 Parts 1 & 3 & 4 (2012)
Water Tightness and Air Tightness:		
Resistance to Flow (ISO 7390)	≤3mm	EN 15651 Parts 1 & 3 (2012)
Loss of Volume (ISO 10563)	≤10%	EN 15651 Parts 1 & 3 & 4 (2012)
Elastic Recovery (ISO 7389)	≥60%	EN 15651 Parts 1 & 4 (2012)
Tensile properties at maintained extension (ISO 8340)	No Failure (NF)	EN 15651 Part 4 (2012)
Tensile properties at maintained extension after water immersion (ISO 10590)	No Failure (NF)	EN 15651 Parts 1 & 3 (2012)
Tear Resistance (ISO 8340 Modified)	NPD	EN 15651 Part 4 (2012)
Microbial Growth (ISO 846 – Procedure B)	NPD	EN 15651 Part 3 (2012)
Durability	No Failure (NF)	EN 15651 Parts 1 & 3 & 4 (2012)

Conditioning: **Method B** Test substrate(s): **Aluminium (no primer)**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Katherine Brown: Technical Manager (R&D)
At Sheffield (UK) on 14th November 2022



Declaration of Performance

No: DOP-G129UK

Unique identification code of the product-type:	G129-UK – The Works Pro
Intended use/es:	Sealant for non-structural façade interior and exterior applications EN 15651-1: F EXT-INT and Non-structural Sanitary applications EN15651-3: XS and Non-structural Pedestrian Walkway Interior applications EN15651-4: PW-INT
Manufacturer:	Sherwin-Williams UK Limited, Thorncliffe Park, Chapeltown, Sheffield, S35 2YP
System/s of AVCP:	System 3
Designated Standard:	Sealant intended for Non-structural Facade Exterior Interior applications EN 15651-1 (2012) and Non-structural Sanitary applications EN15651-3 (2012) and Non-structural Pedestrian Walkway Interior applications EN15651-4 (2012)
Approved Body:	2538 - 4ward Testing Ltd

Declared performance:

Characteristic	Declared Performance	Harmonised Standard
Reaction to fire (EN ISO 11925-2)	NPD	EN 15651 Parts 1 & 3 & 4 (2012)
Release of chemicals dangerous to the environment and health	See product safety data sheet (SDS)	EN 15651 Parts 1 & 3 & 4 (2012)
Water Tightness and Air Tightness:		
Resistance to Flow (ISO 7390)	≤3mm	EN 15651 Parts 1 & 3 (2012)
Loss of Volume (ISO 10563)	≤10%	EN 15651 Parts 1 & 3 & 4 (2012)
Elastic Recovery (ISO 7389)	≥60%	EN 15651 Parts 1 & 4 (2012)
Tensile properties at maintained extension (ISO 8340)	No Failure (NF)	EN 15651 Part 4 (2012)
Tensile properties at maintained extension after water immersion (ISO 10590)	No Failure (NF)	EN 15651 Parts 1 & 3 (2012)
Tear Resistance (ISO 8340 Modified)	NPD	EN 15651 Part 4 (2012)
Microbial Growth (ISO 846 – Procedure B)	NPD	EN 15651 Part 3 (2012)
Durability	No Failure (NF)	EN 15651 Parts 1 & 3 & 4 (2012)

Conditioning: **Method B** Test substrate: **Aluminium (no primer)**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Katherine Brown: Technical Manager (R&D)
At Sheffield (UK) on 14th November 2022