



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: 705/1-CPR/ 2013**

1. Identification Code	<b>Everbuild 705 Rapid Set/Feb Fastset</b> <b>CODES: RAPID10 , RAPID20, FBFASTSET10, FBFASTSET20</b>
2. Type, Batch and/or Serial Number	<b>- For batch number - see packaging</b>
3. Intended use	<b>fast setting cementitious tile adhesive with reduced slip for internal and external use</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 3</b>
7. Notified Body and Tasks	<b>CERAM UK - Initial Type testing</b> <b>Notified Body Ref; 1289</b> <b>Test report reference: 125162-22431</b>
8. European Technical Assessment	<b>Not Applicable</b>
9. Declared Performance	<b>EN 12004: 2007 +A1 2012 - C1FT</b>
Classification	<b>C1FT</b>
Reaction to fire	<b>Class E</b>
Release of dangerous substances	<b>See MSDS</b>



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

Reduced Slip	$\leq 0.5\text{mm}$
<b>Bond Strength as:</b>	
Early tensile adhesion strength	$\geq 0.5\text{N/mm}^2$
Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$
Open time tensile adhesion strength (20 mins)	$\geq 0.5\text{N/mm}^2$
<b>Durability as</b>	
Tensile adhesion after heat aging	$\geq 0.5\text{N/mm}^2$
Tensile adhesion after water immersion	$\geq 0.5\text{N/mm}^2$
Tensile adhesion after freeze thaw cycling	$\geq 0.5\text{N/mm}^2$
Notified body reference	<b>1289</b>

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/2013