



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: 711/1-CPR/ 2013

| | |
|--|--|
| 1. Identification Code | Everbuild 711 Rapid Set Flexiplus/ Feb Fastset Plus CODES: RSPLUS, RSPLUS10, FBFASTPLUS20 |
| 2. Type, Batch and/or Serial Number | - For batch number - see packaging |
| 3. Intended use | Improved fast setting deformable cementitious tile adhesive with reduced slip and open time for internal and external use |
| 4. Manufacturer | Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW U.K |
| 5. Authorised Representative | Not Applicable |
| 6. Assessment and Verification of Constancy of Performance | System 3 |
| 7. Notified Body and Tasks | CERAM UK - Initial Type testing Notified Body Ref; 1289 Test report reference: 13350-1507 |
| 8. European Technical Assessment | Not Applicable |
| 9. Declared Performance | EN 12004: 2007 +A1 2012 - C2FTE S1 |
| Classification | C2FTE S1 |
| Reaction to fire | Class E |



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

| | |
|---|------------------------------|
| Release of dangerous substances | See MSDS |
| Reduced Slip | ≤ 0.5mm |
| Bond Strength as: | |
| Early tensile adhesion strength | ≥ 0.5N/mm² |
| Initial tensile adhesion strength | ≥ 1N/mm² |
| Open time tensile adhesion strength (30 mins) | ≥ 0.5N/mm² |
| Durability as | |
| Tensile adhesion after heat aging | ≥ 1N/mm² |
| Tensile adhesion after water immersion | ≥ 1N/mm² |
| Tensile adhesion after freeze thaw cycling | ≥ 1N/mm² |
| Transverse deformation | > 2.5mm |
| Notified body reference | 1289 |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/2013