

Declaration of Performance

TechFast Window Screw - Cill Screw Self-drilling

Document Number: DOPTF719

1. Unique identification code of the product-type:

TechFast Window Screw - Cill Screw Self-drilling

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Head: Bugle. Recess: Torx. Full/Partial Thread. Material 10B21

3. Intended use or uses of the construction product, in accordance with the applicable harmonised/designated technical specification, as forseen by the manufacturer:

For fastening window/door cills to metal reinforced PVCu

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ForgeFix Ltd. Galleon Blvd, Crossways Bus. Park, Dartford, Kent DA2 6QE, UK.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Tucks Fasteners Ltd. Century Bus. Park, 10 St Margaret's Rd, Dublin, D11 TN80, IE.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP System 4

7. Harmonised / Designated standard:

EN 14566:2008+A1:2009

8. Notified body/ies:

Notified Body: N/A

European Technical Assessment: N/A

9. Declared performance/s:

TechFast Window Screw Cill Screw Self-drilling - Flexural Strength Test

Size	Sample Screw No.	Breakage or Cracking
4.2mm	1-50	Pass

Summary: Pass: 50 pcs Fail: 0 pcs

TechFast Window Screw Cill Screw Self-drilling - Withdrawal Test 4.2mm

No.	Withdrawal Force
1	567N
2	554N
3	591N
4	565N
5	580N
6	577N
7	578N
8	580N
9	574N
10	576N
11	578N
12	555N
13	566N

No.	Withdrawal Force
14	580N
15	578N
16	560N
17	565N
18	566N
19	568N
20	554N
21	555N
22	581N
23	580N
24	582N
25	584N
26	567N

No.	Withdrawal Force
27	554N
28	558N
29	560N
30	568N
31	569N
32	591N
33	587N
34	584N
35	581N
36	570N
37	574N
38	558N
39	577N

No	Withdrawal Force
40	560N
41	571N
42	561N
43	580N
44	574N
45	568N
46	574N
47	573N
48	563N
49	579N
50	574N

Summary: Pass: 50 pcs Fail: 0 pcs

Test Result: PASS

TechFast Window Screw Cill Screw Self-drilling - Point Test (Drilling Performance) 4.2mm

No.	Drilling Time
1	2.18s
2	2.02s
3	2.19s
4	1.98s
5	2.00s
6	1.90s
7	2.12s
8	2.17s
9	1.99s
10	2.17s
11	2.15s
12	2.17s
13	2.15s

No.	Drilling Time
14	2.14s
15	1.95s
16	2.11s
17	1.98s
18	1.94s
19	1.98s
20	1.99s
21	2.14s
22	1.90s
23	1.89s
24	2.15s
25	2.10s
26	1.99s

No.	Drilling Time
27	1.97s
28	1.95s
29	1.91s
30	2.15s
31	2.04s
32	2.07s
33	1.98s
34	2.06s
35	1.98s
36	1.91s
37	2.05s
38	1.94s
39	2.12s

No	Drilling Time
40	1.97s
41	2.20s
42	1.89s
43	2.01s
44	2.06s
45	1.95s
46	2.05s
47	2.12s
48	2.04s
49	2.07s
50	1.99s

Summary: Pass: 50 pcs Fail: 0 pcs

Test Result: PASS

TechFast Window Screw Cill Screw Self-drilling - Length Test (Dimension Measurement) 4.2 x 65mm

No.	Length
1	65.26mm
2	63.60mm
3	65.50mm
4	64.50mm
5	66.00mm
6	64.10mm
7	65.40mm
8	64.00mm
9	64.80mm
10	65.79mm
11	65.88mm
12	64.80mm
13	66.00mm

No.	Length	N
14	64.80mm	2
15	65.80mm	2
16	65.78mm	2
17	66.68mm	3
18	64.58mm	3
19	64.78mm	3
20	65.89mm	3
21	64.87mm	3
22	65.89mm	3
23	64.78mm	3
24	65.81mm	3
25	65.49mm	3
26	66.12mm	3

No.	Length
27	63.88mm
28	64.78mm
29	65.89mm
30	66.10mm
31	64.74mm
32	65.89mm
33	64.58mm
34	65.78mm
35	64.58mm
36	64.78mm
37	66.12mm
38	64.58mm
39	65.12mm

No	Length
40	65.36mm
41	65.89mm
42	65.78mm
43	65.74mm
44	66.15mm
45	63.90mm
46	64.25mm
47	64.58mm
48	64.79mm
49	64.28mm
50	65.48mm

Summary: Pass: 50 pcs Fail: 0 pcs

Test Result: PASS

TechFast Window Screw Cill Screw Self-drilling - Hardness Test 4.2mm

No.	Hardness
1	58.1 HRC
2	57.1 HRC
3	55.8 HRC
4	55.3 HRC
5	57.9 HRC
6	56.9 HRC
7	58.7 HRC
8	56.8 HRC
9	57.8 HRC
10	55.8 HRC
11	58.1 HRC
12	57.2 HRC
13	55.7 HRC

No.	Hardness
14	56.1 HRC
15	56.2 HRC
16	59.9 HRC
17	58.4 HRC
18	56.2 HRC
19	57.8 HRC
20	56.8 HRC
21	55.7 HRC
22	57.8 HRC
23	58.7 HRC
24	57.9 HRC
25	55.9 HRC
26	57.8 HRC

No.	Hardness
27	55.9 HRC
28	56.1 HRC
29	57.0 HRC
30	56.2 HRC
31	56.0 HRC
32	57.2 HRC
33	56.4 HRC
34	55.9 HRC
35	58.7 HRC
36	55.4 HRC
37	56.8 HRC
38	57.4 HRC
39	56.6 HRC

No	Hardness
40	58.2 HRC
41	57.4 HRC
42	57.7 HRC
43	56.9 HRC
44	56.7 HRC
45	56.2 HRC
46	56.9 HRC
47	57.3 HRC
48	56.8 HRC
49	57.1 HRC
50	56.3 HRC

Summary: Pass: 50 pcs Fail: 0 pcs

Test Result: PASS

This declaration of performance is issued u	under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of:	
Place of issue:	ForgeFix Ltd.
Date of issue:	ForgeFix Ltd. Galleon Blvd, Crossways Bus. Park, Dartford, Kent DA2 6QE, UK.
	01/01/2021
Name:	Anthony Armitt
Position:	Commercial Director
Signature:	
	1 the

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.