

DECLARATION OF PERFORMANCE

DoP No: S55001026-0043

1. Unique identification code of product-type:
OB1 Multi-Surface Construction Sealant & Adhesive - Colours
2. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Sealants for façade elements
Sealants for sanitary joints
Sealants for pedestrian walkways
EN 15651-1:2012 : F-EXT-INT-CC (CLASS 25HM)
EN 15651-3 : 2012: S (CLASS XS2)
EN 15651-4 :2012: PW-EXT-INT-CC (CLASS 25 HM)
3. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):
SIROFLEX LIMITED ■ DODWORTH BUSINESS PARK, DODWORTH, BARNSELY, S. YORKS ■ S75 3SP
4. System or systems of assessment and verification of constancy of performance:
System 3
5. Designated Standards
EN 15651-1 / EN 15651-3 / EN 15651-4
6. Approved Body
2538, 4ward Testing Ltd

7. Declared performance:

Conditioning: Procedure B

Substrate: Mortar M1 (with primer MSP)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN ISO 11925-2:2020)	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow (EN ISO 7390)	≤ 3 mm	
Loss of volume (EN ISO 10563)	≤ 10 %	
Tensile properties at maintained extension after water immersion (EN ISO 10563)	NF	
Tensile properties (secant modulus) for use in cold climate areas (-20°C) (EN ISO 8340)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C) (EN ISO 8340)	NF	
Durability	Pass	

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN ISO 11925-2:2020)	Class E	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Vertical flow resistance (EN ISO 7390)	≤ 3 mm	
Loss of volume (EN ISO 10563)	≤ 20 %	
Tensile properties at maintained extension after water immersion (EN ISO 10590)	NF	
Microbiological growth (EN ISO 846)	NPD	
Durability	Pass	

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN ISO 11925-2:2020)	Class E	EN 15651-4:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Tensile properties at maintained Extension (EN ISO 8339)	≤ 3 mm	
Loss of volume (EN ISO 10590)	≤ 10 %	
Tear resistance (EN ISO 8340)	NF	
Tensile properties (secant modulus) for use in cold climate areas (-20°C) (EN ISO 8340)	NF	
Tensile properties at maintained extension for use in cold climate areas (-30°C) (EN ISO 8340)	NR	
Durability	Pass	

(*) See material safety data sheet
NPD: No Performance Determined
NF: No Failure
NR: Not required

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Ashley Greenwood
HSE Manager
Siroflex Limited

December 2019